

QUIC-KIT®

The McKissick® QUIC-KIT®

Featuring the McKissick® 750 Bridge Crane Block

The patented McKissick® QUIC-KIT® system is a revolutionary concept that provides you the ability to build a factory quality replacement bridge crane block where you need it, when you need it.

The QUIC-KIT® system provides the components needed to build up to 32 possible combinations of a 750 bridge crane block; all in one kit that can be easily assembled on site.

Features of the McKissick® QUIC-KIT® include:

- **Reduced downtime** — A replacement block can be assembled in minutes from kit components utilizing tools and assembly instructions provided in each kit.
- **Multiple versions of two sheave blocks** — Up to 32 possible block combinations are included in the 752 series block kit. Each kit contains three wire line sizes and two center pins with multiple sheave spacers.
- **Adjustable sheave spacing in 1/2" increments** — Center pin design gives you the ability to assemble the replacement block to meet your spacing requirement.
- **The McKissick® QUIC-KIT®** — Comes complete in a durable carrying case for easy transport and for storing components on the work site or warehouse.

Crosby has established a call center to answer questions concerning the QUIC-KIT®, 750 series blocks or other McKissick® blocks. To reach the call center, simply call (800) 727-1555.



WLL (t)	751K Stock No.	Sheave O.D. (in.)	Pitch Diameter		Sheave Wire	
			(in.)	(mm)	(in.)	(mm)
2	1003542	6.5	5.69	151	1/4, 5/16, 3/8	6.5, 8, 9-10
3	1003551	8	7.38	187	1/4, 5/16, 3/8, 7/16, 1/2	6.5, 8, 9-10, 11, 12-13
5	1003560	10	9.25	235	3/8, 7/16, 1/2, 9/16, 5/8	9-10, 11, 12-13, 14, 16
7.5	1003579	12	11.00	279	1/2, 9/16, 5/8, 3/4	12-13, 14, 16, 19
10	1003588	14	12.50	318	5/8, 3/4, 7/8, 1	16, 19, 22, 25-26

WLL (t)	752K Stock No.	Sheave O.D. (in.)	Sheave Spacing Centerline		Pitch Diameter		Sheave Wire	
			(in.)	(mm)	(in.)	(mm)	(in.)	(mm)
3	1003595	6.5	3.25-5	82.6-127	5.95	150-152	1/4, 5/16, 3/8	6.5, 8, 9-10
5	1003604	8	4.5-6.5	114-165	7.38	183-191	1/4, 5/16, 3/8, 7/16, 1/2	6.5, 8, 9-10, 11, 12-13
7.5	1003613	10	5.25-7.75	133-203	9.25	228-236	3/8, 7/16, 1/2, 9/16, 5/8	9-10, 11, 12-13, 14, 16
10	1003622	12	6.5-10	165-254	11	273-282	1/2, 9/16, 5/8, 3/4	12-13, 14, 16, 19
15	1003631	12	7.5-11	191-279	11	273-282	1/2, 9/16, 5/8, 3/4	12-13, 14, 16, 19



Promotional Code

McKISSICK®
Your Total Block Company

CROSBY PRODUCTS DISTRIBUTED BY:

Imperial / Metric

McKissick® Overhead Bridge Crane Blocks



SEE APPLICATION AND WARNING INFORMATION

Para Español: www.thecrosbygroup.com

McKissick® Easy-Lift® Overhead Bridge Crane Blocks

- Wide range of product available (see tables below).
- Removable housing allows block to be reeved without complete disassembly.
- Bearing life and Design Factors meet:
 - ASME HST-4, Class H
 - CMAA 70 Class D
 - FEM9.511 Class 2m
 - ISO 4301.1 Class M5
- Adjustable sheave spacing in 1/2" increments (1/4" on 6 1/2 size).
- Sheave pitch diameter minimum of 16 times rope diameter on standard sizes.
- All single point shank hooks are genuine Crosby®, forged alloy steel, Quenched and Tempered, contain the patented QUIC-CHECK® markings and come with a world class latch that integrates with hook tip.
- U.S. Patent 7,255,330
- All sizes are **RFID EQUIPPED**.

- Sheave bearings are maintenance free and sealed for life (10,000 hrs.).
- Ability to attach optional anti two-block device.
- Available with shackle as lower connection point.
- Ultimate load is 5 times the Working Load Limit.

Key to McKissick® Easy-Lift® Overhead Bridge Crane Blocks					
Single and Double Sheave Blocks				Double Sheave Blocks Only	
BC	05	D	08	B	36
↑	↑	↑	↑	↑	↑
McKissick® 750 Series Bridge Crane Blocks	Working Load Limit (t)	Number of Sheaves S = 1 D = 2	Sheave Diameter (in.)	Center Pin Designation	Sheave Spacing in 1/8" Increments



BC-751-Single Sheave

Model 751 - Single Sheave						
WLL (t)	2	3	5	7.5	10	
Sheave O.D.	6.5" 165mm	8" 203mm	10" 254mm	12" 305mm	14" 356mm	
Pitch Diameter	5.69" 151mm	7.38" 187mm	9.25" 235mm	11" 279mm	12.5" 318mm	
Wire Line*						
1/4" 6.5mm						
5/16" 8mm						
3/8" 9 - 10mm						
7/16" 11mm						
1/2" 12 - 13mm						
9/16" 14mm						
5/8" 16mm						
3/4" 19mm						
7/8" 22mm						
1" 25 - 26mm						



BC-751

BC-752 - Double Sheave

Model 752 - Double Sheave						
WLL (t)	3	5	7.5	10	15	
Sheave O.D. (mm)	6.5" 165mm	8" 203mm	10" 254mm	12" 305mm	12" 305mm	
Sheave Spacing Centerline (mm)	3.25" - 5" 82.6 - 127mm	4.5" - 6.5" 114 - 165mm	5.25" - 7.75" 133 - 203mm	6.5" - 10" 165 - 254mm	7.5" - 11" 191 - 279mm	
Pitch Diameter (mm)	5.95" 150 - 152mm	7.38" 183 - 191mm	9.25" 228 - 236mm	11" 273 - 282mm	11" 273 - 282mm	
Wire Line*						
1/4" 6.5mm						
5/16" 8mm						
3/8" 9 - 10mm						
7/16" 11mm						
1/2" 12 - 13mm						
9/16" 14mm						
5/8" 16mm						
3/4" 19mm						



BC-752

* Additional wireline sizes available.

= Primary Wire Line Size = Other Wire Line Sizes