

# PEGA MODULAR MATERIAL HOIST WITH EXPENDIBLE PLATFORM

PIONEER IN INNOVATION

QUALITY – RELIABILITY – USER FRIENDLY

PEGA "PLC" – Programmable Landing Control for exact stops for 100 floors

PEGA "LDS" - Load Detection System – brings up to 70% lower power consumption and higher speed

PEGA "FIS" - Fault Indication System

HOT DIP GALVANIZED CAGES WITH STEEL FLOOR AND ALL ACCESSORIES FOR UNLIMITED LIFETIME - ALL AS STANDARD

## PEGA 27ME VFC

### TECHNICAL DATA

Payload capacity	lb	6,000
Speed	ft/min	0 - 130
Rated lifting height	ft	330
Max. tie spacing	ft	30

### CAGE DIMENSIONS


Internal width	4'-11.1"
Internal length	10'-6.0"
Internal height	3'-7.3"

### ELECTRICAL DATA

Power supply range	480V 60Hz 3Ph
Power supply fuse	50A
Motor machinery	PEGA/SEW
Starting current	34A
Power consumption	49kVA
Cable guiding system	Cable trolley

### WEIGHTS

Cage	lb	3,530
Mast section with one/two racks	lb	280/330
Mast section length		4'-11.3"



### GENERAL

Platforms equipped with frequency controlled drives and programmable control system.

#### Variety of optional equipment:

Adaptable mast tie systems.

Different dimensions and capacities or executions on request.

Easy self-climbing mast tower.

The above specification may vary based on customer's request.

**Norms and regulations:** EN 1495 or ANSI

### CONTROL SYSTEM

Joystick or keypad control.



## CONSULT - SALE - SERVICE

### PEGA HOIST Ltd.

Fáblovka 547  
CZ – 533 52 Pardubice  
Tel.: +420 466 536 348-50  
Fax.: +420 466 536 351  
E-mail: info@pega-hoist.com  
www.pega-hoist.com

### Local representative:

