

Fowler-Bowers XT-Series Holemikes

BEST SELL

The Fowler-Bowers range of mechanical two and three point bore micrometers are now available as XT extended travel holemikes, allowing a wide measurement range without the need to interchange anvils.



Special Features:

- Graduations 0.00025"
- · 3-pt contact with tungsten carbide measuring anvils above .5"
- Blind bore measuring above .5"
- · Ratchet stop for consistent measuring

SPECIAL DEAL!

- Non-removable anvils
- · Extensions available for deep measuring
- Setting rings included in all sets
- Includes UKAS certificates for all Holemikes and setting rings
- Every gage is individually serialized
- · Special anvils available, contact the Fowler Technical Department

				Meas.	Ring	List	Sale
Order No.	Range	Grads.	Accuracy	Depth	Included	Price	Price
52-255-310-0	.250"312"	.00025"	.00015"	2.28"	.312"	\$695.30	\$486.71
52-255-311-0	.312"375"	.00025"	.00015"	2.28"	.312"	643.80	450.66
52-255-312-0	.375"500"	.00025"	.00015"	2.28"	.5"	643.80	450.66
52-255-313-0	.500"625"	.00025"	.00015"	2.44"	.5"	643.80	450.66
52-255-314-0	.625"750"	.00025"	.00015"	2.44"	.75"	660.20	462.14
52-255-315-0	.750"-1"	.00025"	.00015"	2.60"	.75"	725.10	507.57
52-255-316-0	1"-1.375"	.00025"	.00015"	2.60"	1.375"	1033.10	723.17
52-255-317-0	1.375"—2"	.00025"	.00015"	3.15"	1.375"	1057.80	740.46
52-255-318-0	2"-2.625"	.00025"	.0002"	3.15"	2.625"	1261.80	883.26
52-255-319-0	2.625"-3.250"	.00025"	.0002"	3.15"	2.625"	1273.10	891.17
52-255-320-0	3.250"-4"	.00025"	.0002"	3.94"	3.25"	1588.30	1111.81

Fowler-Bowers XT-Series Holemike Sets

Order No.	Range	Includes	List Price	Sale Price
52-255-565-0	.250"375"	2 heads, 2 handles, 1 ring	\$1544.00	\$1080.80
52-255-665-0	.375"750"	3 heads, 3 handles, 2 rings	1758.20	1230.74
52-255-775-0	.750"-2"	3 heads, 3 handles, 2 rings	2762.50	1933.75
52-255-885-0	2"-4"	3 heads, 3 handles, 2 rings	3745.10	2621.57

FOWIER TOOL-A-THON

Ultra-Cal V Electronic Calipers

	Top-of-the-line Caliper! Fowler's BEST Caliper!	
	100 120 10 , 100 , 100 Ultra Cal V 🚫 💱	
54-100-067-1		7
- 4-way measurement, inside, outside, depth and step. (6" & 8" models) - Resolution: .0005"/.01mm - Direct inch/metric conversion	 Hardened stainless steel constructio Direct RS-232 output Features Absolute/Relative Measurin Modes Hold function Thumbroll (6" model only) 	

- Temperature range 5 to 40C° working; -20 to 60C° in storage

NEW!

- Includes case

Order No.	Description	Accuracy	Resolution	List Price	Sale Price
54-100-067-1	6"/150mm	0.0008"/20µm	0.0005"/.01mm	\$194.70	\$144.00
54-100-068-1	8"/200mm	0.0012"/30µm	0.0005"/.01mm	463.50	401.70
54-100-069-1	12"/300mm	0.0012"/30µm	0.0005"/.01mm	556.20	504.70
BLUETOOTH MC	DDELS				
54-100-167-0	NEW 6"/150mm	0.0008"/20µm	0.0005"/.01mm	324.50	288.40
54-100-168-0	NEW 8"/200mm	0.0012"/30µm	0.0005"/.01mm	602.60	540.80
54-100-169-0	NEW 12"/300mm	0.0012"/30µm	0.0005"/.01mm	803.40	638.60

Rapid-Mic Electronic Micrometers

Auto On/Off Position recall IP67 with or without of Delrin quick displace Adjustable measuring	data cable. ment thimble g force, 5N/10N	DE U ST	4-815-030-0 Spindle Mover ed Range!	NEW! ment! Save 20%
Menu customizable v Non-rotating spindle USB output Carbide anvils	vith free software		54-815-1	AAA A
• Extended Range 0-3	0mm, 30-66mm and 66 ciality micrometers are nical Department.			Heo i
Order No.	Description	Max Error	List Price	Sale Price
54-815-030-0	0-1.18"/0-30mm	0.00012"/.003mm	\$504.70	\$399.00
54-815-060-0	1.18"-2.6"/30-66mm	0.00016"/.004mm	746.80	700.40
54-815-100-0	2.6"-4.0"/66-102mm	0.00020"/.005mm	1044.40	942.50
BLUETOOTH MODEL				
54-815-130-0 Set	NEW 0-1.18"/0-30mm	0.00012"/.003mm	746.80	669.50
54-815-111-0	0-4"/0-102mm		2307.20	2034.00

Prices & Specifications are subject to change without notice.

TOOL-A-THON



Fowler TOOL-A-THON

Swiss-Style Micrometers

Fowler	20 013 52-229-201-0	OO01" readin Carbide mea Insulated fran Ratchet thiml Microfine gra Sizes over 1" Meets or exc Includes case	suring faces ne ole and lockin duations 'include stand eeds Federal	dard
0-1" 0.0001"	Save Order No. 52-229-201-0 52-229-202-0 52-229-203-0 52-229-203-0 52-229-204-0 52-229-204-0 52-229-205-0 52-229-206-0) 1-2") 2-3") 3-4") 4-5"	List Price \$40.30 47.20 58.20 66.80 82.50 96.90	Sale Price \$28.30 34.50 39.50 44.50 52.50 63.50
Swiss Style		.0001" reading Carbide meass Ratchet thimbl Microfine grad Sizes over 1" i Meets or exce Sizes over 1" i Meets or exce Sizes over 1" i	uring faces e and locking uations nclude standa	nut ard pecifications na ned "
Order No. 52-229-213-0 52-229-214-0 52-229-220-0	Range 0-3" set 0-4" set 0-100mm set		List Price \$145.30 223.80 223.80	<u>Sale Price</u> \$100.00 150.00 150.00
	52-224-001-0 Save over 40% 52-224-001-0 52-224-002-0 52-224-003-0	 Resolutior Microfine g Carbide tig Positive lo Sizes over Includes c Range 0-1" 1-2" 2-3" 	pped measurii cking nut on s r 1" include st ase <u>List Price</u> \$91.10 95.70 109.00	ng vernier) n satin chrome ng faces spindle andard Sale Price \$54.00 56.90 65.00
Digit Counter		Digital counter Resolution: .00 Microfine gradu Carbide tipped Ratchet thimble Positive locking Sizes over 1" s	01" (.01mm o lations on sat measuring fa e g nut on spind	n metric set) in chrome. ces le tandards n a e ned "
Order No. 52-224-103-0 52-224-104-0 52-224-220-0	Range 0-3" set 0-4" set 0-75mm set Prices & Specifications are subject		ist Price \$302.80 407.80 302.80	<u>Sale Price</u> \$165.00 230.00 165.00 5

Wer TOOL-A-THON

Outside Inch Micrometers



Fowler micrometers are of the finest quality available, at prices that defy competition. Special care in design and workmanship create a long lasting precision tool.

- · Hammertone blue baked enamel finish.
- Microfine graduations on satin chrome finish and carbide tipped measuring faces.
- · Diameter of measuring faces: .256"
- · Graduation: .0001'
- Flatness: .00003"
- · Quick, easy zero adjustment on sleeve.
- · Positive lever locking clamp
- · Spindle thread hardened, ground and lapped for ultimate accuracy.
- · Anvil & spindle hardened and precision ground with microlap finish on tips.
- · Includes a wrench and case.

Order No.	Range	Graduation	Accuracy	Thimble	List Price	Sale Price
52-240-101-1	NEW 0-1"	0.0001"	±.00015"	Ratchet	\$35.70	\$30.40
52-240-102-1	NEW 1-2" w/standard	0.0001"	±.00015"	Ratchet	41.50	35.30
52-240-003-1	NEW 2-3" w/standard	0.0001"	±.0002"	Ratchet	48.50	41.20
52-240-004-1	NEW 3-4" w/standard	0.0001"	±.0002"	Ratchet	54.20	46.10
52-240-005-1	NEW 4-5" w/standard	0.0001"	±.00025"	Ratchet	60.00	51.00
52-240-006-1	NEW 5-6" w/standard	0.0001"	±.00025"	Ratchet	65.80	55.90
52-240-007-1	NEW 6-7" w/standard	0.0001"	±.0003"	Ratchet	71.50	60.80
52-240-008-1	NEW 7-8" w/standard	0.0001"	±.0003"	Ratchet	84.20	71.60
52-240-009-1	NEW 8-9" w/standard	0.0001"	±.0003"	Ratchet	95.70	81.40
52-240-010-1	NEW 9-10" w/standard	0.0001"	±.0003"	Ratchet	108.50	92.20
52-240-011-1	NEW 10-11" w/standard	0.0001"	±.00035"	Ratchet	120.00	102.00
52-240-012-1	NEW 11-12" w/standard	0.0001"	±.00035"	Ratchet	131.50	111.80
SETS						
52-215-003-1	NEW 0-3" w/standards	0.0001"			144.20	114.00
52-215-004-1	NEW 0-4" w/standards	0.0001"			198.40	157.60
52-215-006-1	NEW 0-6" w/standards	0.0001"			305.70	243.10
52-215-012-1	NEW 0-12" w/standards	0.0001"			918.20	595.30
52-215-612-1	NEW 6-12" w/standards	0.0001"			629.80	450.00

Fowler TOOL-A-THON

6

Large Capacity Inch Micrometers

Fowler's Large Carpacity Inch Micrometers are used for larger applications and is available in sizes up to a 20". Each micrometer offers superior design and workmanship to ensure high precision and long life — and at economical prices.



- · Hammertone blue baked finish
- · Microfine graduations on satin chrome finish and carbide tipped measuring faces.
- Diameter of measuring faces: 0.295"
- · Ratchet stop thimble for exact and repetitive readings
- Flatness: 0.00003"
- · Quick, easy zero adjustment on sleeve
- · Positive lever locking clamp ensures reliable measurement setting at all times
- Anvil & spindle hardened and precision ground with microlap finish on tips
- · Includes standard
- · Includes a wrench and case

Order No.	Range	Graduation	Accuracy	List Price	Sale Price
52-240-013-0	NEW 12-13" w/standards & case	0.001"	0.00044"/0.011mm	\$301.00	\$240.00
52-240-014-0	NEW 13-14" w/standards & case	0.001"	0.00044"/0 <mark>.011mm</mark>	336.30	268.00
52-240-015-0	NEW 14-15" w/standards & case	0.001"	0.00044"/0.011mm	346.10	276.00
52-240-016-0	NEW 15-16" w/standards & case	0.001"	0.00044"/0 <mark>.011mm</mark>	378.40	302.00
52-240-017-0	NEW 16-17" w/standards & case	0.001"	0.0005"/0. <mark>013mm</mark>	388.80	310.00
52-240-018-0	NEW 17-18" w/standards & case	0.001"	0.0005"/0. <mark>013mm</mark>	422.20	337.00
52-240-019-0	NEW 18-19" w/standards & case	0.001"	0.0005"/0. <mark>013mm</mark>	446.50	356.00
52-240-020-0	NEW 19-20" w/standards & case	0.001"	0.0005"/0. <mark>013mm</mark>	534.10	427.00

Micrometer Stands

52-247-000-0 • Adjust micrometer stand to any position.

- · Hammertone blue baked enamel base.
- Provides a measuring position and angle for outside micrometers and other instruments.

52-247-005-0



Micrometer shown

not included

- Unique locking nut adjusts micrometer stand to any position for perfect use and viewing.
- Stand folds for storage.
- · Hammertone silver baked enamel base.
- Provides a measuring position and angle for outside micrometers and other instruments.

52-247-010-0

- · Holds standard 0-12" micrometers firmly to metal surfaces
- Use at machine centers, work, assembly and inspection stations, steel tables and shelves

V-bottom for mounting on cylindrical surfaces

- On/Off magnet switch
- Blue enamel finish
- Base is 2.30" L x 1.20" W x 3.50" H

Order No.	Description	List Price	Sale Price
52-247-000-0	Adjustable Micrometer Stand	\$50.80	\$33.00
52-247-005-0	Folding Micrometer Stand	34.00	24.20
52-247-010-0	Magnetic Micrometer Stand	50.00	41.20

Volume 15

6.5

7

Digit Co	ounter Ba	ll Anvil	Micro	ometer	S	
	52-1 NFW!	244-201-1 Save 15%	to .00 • No. 52 sion g face • No. 52 sion g • The s inside	01" 2-244-201-1 sj pround with a c 2-244-301-1 a pround pherical anvil o	s to .001"; slee pindle hardene carbide tipped nvil is hardene or spindle com ce at a single p	ed and preci- measuring ed and preci- tacts the
			 Spind Ratch 	le thread hard	ened, ground e on all models on spindle	
Order No.	Description		Graduation	Accuracy	List Price	Sale Price
	NEW Ball Anvil NEW Ball Anvil & Spind	0-1" le 0-1"	0.0001" 0.0001"	0.00016" 0.00016"	\$95.70 101.50	\$81.25 86.10
	15%	52-246-001-1 NEW!	Anvil 8 with n Non-re Ratch Blade blade Accura	& spindle hard nicrolap finish otating spindle et thimble	9)30"; blade wid .315" or 0—1"	ion ground
Order No.	Panga	Graduation	A	uracy	List Price	Sale Price
52-246-001-1	Range NEW 0-1"	0.0001"		0016"	\$171.70	\$143.20
52-246-002-1	NEW 1-2"	0.0001"	0.00	0016"	186.90	152.90
Disc Mi		52-250-111-1 Save 15%	 close more Anvil groun faces Posit Ratcl Flatn Accur 	and spindle a and spindle a and with microla ive lever lockin net thimble ess: .00004"	llelism: 1" & 2"	ys, fins and nd precision easuring
Order No.	Range	Graduation	Aco	curacy	List Price	Sale Price
52-250-111-1 52-250-112-1	NEW 0-1" NEW 1-2"	0.0001" 0.0001"		0016" 0016"	\$90.00 101.50	\$76.50 86.10
·	ical and S					
		52-510-601-1 EW!	The any sitioned axis of conven tubings cal wall • Anvil is • Carbid • Spindl lappee • Positiv	vils of tube m d at a 90° ang the spindle, r ient for meas and other wo s. s hardened an le tipped spinc e thread is har	icrometers an le in respect naking it praces suring wall this orkpieces with d precision grad the rdened, ground	re po- to the stical and ickness of h cylindri- pund.

Order No.	Range	Graduation	Accuracy	Туре	List Price	Sale Price
52-510-601-1	NEW 0-1"	0.0001"	0.00024"	Cylindrical	\$57.70	\$43.30
52-510-602-1	NEW 0-1"	0.0001"	0.00024"	Spherical	117.70	102.00

Extended Range Point Micrometers



- Wrench furnished with each micrometer for fast, easy zero adjustment on the sleeve.
- Flatness: .00003"
- · Parallelism: .00005"
- 52-517-612-1 supplied with a ball anvil.
- Includes case.



Order No.	Range	Graduation	Accuracy	Anvil	Throat Depth	List Price	Sale Price
52-517-611-1	NEW 0-1"	0.0001"	0.00016"	Flat	6"	\$116.50	\$81.00
52-517-612-1	NEW 0-1"	0.0001"	0.0002"	Ball	11.8 <mark>75</mark> "	155.70	108.00

Volume 15.3

9



Fowler's line of fine quality vernier calipers measure accurately in inch or metric with vernier scales of .001" and .02mm.

- Made of fully hardened stainless steel; microfine black graduations on a satin chrome finish for easy, precise reading.
- All models offer a depth rod which can be read directly from verniers.
- · Measuring faces are ground and lapped for extreme accuracy.
- · 4-way jaws for outside, inside, depth and step measurements.
- · Extra-long vernier ensures accuracy.
- · All sliding surfaces are raised to prevent defacement and wear of graduations.
- · All models meet or exceed U.S. Federal specifications for accuracy.

· Includes case.

	and the second			the second second second second	the second second second
Order No.	Range	Graduation	Depth of Jaws	List Price	Sale Price
Vernier Caliper w	vith Fine Adjustment				
52-058-016-0	NEW 0-6"/0-150mm	0.001"/0.02mm	1.6"	\$47.30	\$33.10
52-058-008-0	NEW 0-8"/0-200mm	0.001"/0.02mm	1.9"	69.20	48.00
52-058-012-0	NEW 0-12"/0-300mm	0.001"/0.02mm	2.5"	107.30	75.00
Vernier Caliper w	ith Thumb Lock				
52-059-016-0	NEW 0-6"/0-150mm	0.001"/0.02mm	1.6"	42.70	29.90

Master Vernier Caliper

52-085-012-0

The Fowler line of Master Vernier Calipers—in sizes up to 60"/1500mm permit easy inch and metric measurement of larger workpieces.

These calipers are of the highest quality and accuracy to ensure the utmost in vernier measurement. The complete range of sizes assures you of the perfect choice necessary for your precision applications.

- · Satin chrome finish on all models.
- · Hardened stainless steel throughout; ground and lapped for accuracy.
- Extra long vernier scales have wide spaced microfine graduations on satin chrome finish to ensure easy reading.
- Machine divided and engraved from master for exceptional accuracy.
- A raised sliding surface prevents wear and defacement of microfine graduations.
- · Verniers are adjustable for wear.
- Open face design permits both vernier scales to be located on one side of the gage for both inside and outside measurements.
- All sizes permit inside and outside measurements.
- For larger workpieces, the long jaws permit greater accessibility and easier measurements.
- · All sizes meet or exceed U.S. Federal specifications for accuracy.
- Includes case.

Order No.	Range	Graduation	Jaw Depth	List Price	Sale Price
52-085-012-0	NEW 12"/300mm	0.001"/0.02mm	3"	\$169.60	\$118.70
52-085-024-0	NEW 24"/600mm	0.001"/0.02mm	4"	359.90	249.00
52-085-040-0	NEW 40"/1000mm	0.001"/0.02mm	5-1/2"	842.10	589.45
52-085-060-0	NEW 60"/1500mm	0.001"/0.02mm	7-1/2"	2362.00	1250.00

012341947	Dial Caliper Dial caliper - Solid stainless steel con - Solid stainless steel con - Silky smooth movemen - Dial hand completes or - Dial hand completes or - Dial hand completes or - Thumbroll for rapid sett - Knurled lock assures pr	nstruction t throughout e revolution per each .1 ing	Sa	abi 1 5%	Fowler T00
Order No. 52-008-006-2	Includes fitted case Range 0-6"	Graduation 0.001"	List Price Sa \$134.60	ale Price	ŗ
0 1 1 1 1 1 1 1 0 7 0 0 1 1 1 1 1 1 0 7		1811917199999999999 52-00	BEST SE BEST SE BEST SE TOMLER HIC S2-008-707-0	LLER!	FOOL-A-THON
 4-way measuring Solid stainless sta Silky smooth mov .100"/2mm range .001"/.02mm read 	ement throughout per revolution ling dial face	Sav over 2	52-008-7 e	r14-0	ts
Tough shockproof Supplied in shop-		The state of the state	5. 6 M 250		Vol
Order No. 52-008-704-0 52-008-714-0 52-008-706-0 52-008-707-0 52-008-709-0 52-008-708-0 52-008-712-0	Range 0-4" 0-6" 0-6" 0-150mm (Metric Model) 0-8" 0-12"	Dial Face Color White Black White Black Yellow White White	List Price \$53.00 53.00 72.60 72.60 72.60 91.10 120.60	Sale Price \$41.00 41.00 57.00 57.00 57.00 68.20 92.30	Volume 15.

11

ω

Heavy Duty Dial Calipers

	BEST SELLEN
	untuk untuk (untuk)
	лен ² пальенство ⁰ ¹⁰ вликая элек никонко 52-025-108-0
Graduations: .001"	52-025-108-0
Large .100" one-rev dial	
Depth rod	Save 4
• 4-way measurement	
Cross-jaws for direct international	al measurement
Stainless steel, satin chrom	e finish
Includes wood case	

A-THOA

Order No.	Range	Jaw Length	List Price	Sale Price
52-025-108-0	8" Caliper	2.5"	\$132.10	\$97.30
52-025-112-0	12" Caliper	2.875"	192.10	138.40



	Dial Face	List	Sale
Order No.	Color	Price	Price
52-008-007-0	White	\$87.10	\$50.50
52-008-005-0	Black	84.55	50.50

Extended Range Dial Calipers

Sol-A-THOM BEST SELLER! BALEF HIGH THOM	Satin chrome Depth rod	eel construction e finish Il measuring nibs		08-018 Ve 0%
Order No.	Range	Depth of Jaws	List Price	Sale Price
52-008-018-0	18" Caliper	3.125"	\$239.90	\$183.55
52-008-024-0	24" Caliper	3.375"	290.70	228.00

12

Polv-Cal	[®] Electronic Caliper	Inch/Metric/Fraction	
		Range 6"/150mm	
	-	Polycarbonate frame	
Instaliation (AC	utunluntunluntunluntunluntunluntunl	 Large easy-to-read display 	
inning . 184		Resolution .0005"/.01mm	
CN - OFF - 2290	Polycarbonate Caliper	(Fractions by 1/64" increments)	
		Absolute/Incremental Measurement	
	Fractional Measurement Easy-To-Read Display	Direct inch/metric/fraction conversion 4-way measuring	
	Easy-10-head Display Lightweight frame	Accuracy +/008"	ועו
	TM	Supplied with clip-on vinyl pouch	
	• FRACTION		
Order No.	Description	List Price Sale Price	
54-101-175-0	Poly-Cal Electronic Caliper	\$25.30 \$19.00	
54-100-350-0	CR2032 Battery	5.70	
All them 40	Economy Disitel	Oclinera	FOOL-A-THON
4 thru 12	" Economy Digital	Campers	
	Abooluto Doodin	Absolute sensor technology	
ų ų	<u> </u>		
nn in Otgin		Direct Inch/Metric conversion	
	Fowler	• Accuracy: .001"/.02mm (4" & 6"	
0 = 0 = ABS			
	54-100-000-2	.0015"/.04mm (8" & 12" models)	
		Resolution: .0005"/.01mm	
	20-30% SPC	Large easy-to-read LCD display Includes molded case	
	Direct	• Includes molded case	
Order No.	Range	List Price Sale Price	
54-100-004-2	0-4"/100mm Caliper	\$96.90 \$65.00	
54-100-000-2	0-6"/150mm Caliper	113.00 75.00	
54-100-008-2	0-8"/200mm Caliper	132.70 105.00	
54-100-112-2	0-12"/300mm Caliper	173.00 120.00	
54-100-350-0	CR2032 Battery	5.70	
54-520-399-0	Data Cable	140.00	7
Terrer and the second s	Protected to: Protected to: Protec	Absolute sensor technology Water resistant to IP54 specifications Stainless steel frame Direct Inch/Metric conversion Accuracy: .001"/.02mm (6" models) Resolution: .0005"/.01mm Large easy-to-read LCD display -4-way measurement Includes molded case	
Order No.	Range	List Price Sale Price	
54-100-777-2	0-6"/150mm Electronic IP54 Cali		2TI
54-100-712-2 54-100-350-0	0—12"/300mm Electronic IP54 Ca CR2032 Battery	liper 184.60 130.00 5.70	
54-520-399-0	Data Cable	140.00	
		110.00	
Pro-Max E	lectronic Caliper		
	Absolute Reading	• Maximum Error: .001"/.02mm	
	AUSUILLE MEAUIIIS	Away measurement inside outside	
PRO	D-MAX	 4-way measurement, inside, outside, depth and step 	
0.589s	106 120 5 140 6 mm auth SYLVAC SYSTEM	• Resolution: .0005"/.01mm	
		Repeatability: .0005"/.01mm	
Marco Str.		Range: 6"/150mm	
	👕 🚽 🚽 Save 🚽	Direct inch/metric conversion	
	_over 30%	Temperature range 5 to 40C° work-	
	00 /0	ing; -20 to 60C° in storage	
		 Hardened stainless steel construction 	
	Fowler	RS-232 output	
		Features Absolute/Relative Measur-	
J 10	ANI SPC IP67	ing Modes	
WARR		Hold function	
Swiss Quality!	DIRECT	Includes molded case	Volume 15.
Order No.	Range	List Price Sale Price	
54-200-777-1	0-6"/150mm Pro-Max Electronic Calip		
54-100-350-0	CR2032 Battery	5.70	J
L	,		
54-100-350-0	CR2032 Battery Prices & Specifications are subje	10	ω

XTRA-	VALUE CA	Elect	ronic Ca	lipers	ST.SELLER!
			-	BE	SHER HIGH PRESS
X-SERIE	• Accuracy: .001"/. • Stainless steel fr • Large easy-to-re • Resolution: .000	<i>54-101-15</i> .02mm <i>(6" model</i> ame ad display 5"/.01mm		ABS	
	 Direct inch/metric Absolute/Increme 4-way measuring Includes molded 	ental Measureme	nt Also a Super Large Di	available with splay with Ho	
Order No. 54-101-150-2 54-101-600-1 54-101-200-1 54-101-800-1 54-101-300-1 54-101-900-1 54-101-900-1	Range I 6"/150mm I 6"/150mm I 8"/200mm I 8"/200mm I	Display Type Regular Display Super Large Display Regular Display Super Large Display Regular Display Super Large Display	with hold feature	List Price \$46.40 57.70 69.20 86.50 92.70 115.50 5.70	Sale Price \$34.50 38.60 58.20 66.00 82.90 88.00
	Former EUL	Electro RO-GAL IV 10-330-1			
Protected to: IP554 COOLART & FLID RESISTANT		 Absolute/Increm 	ic/fraction convers nental Measureme to IP54 standards 05"/.01mm 64" increments) rame 19	ion	eal IV 0-332-0 Ve 0%
Order No. 54-100-330-1	Description 6"/150mm Euro-Cal IV Ele		Accuracy .±.001"/.02mm	\$115.30	Sale Price \$80.00
54-100-331-0 54-100-332-0 54-100-350-0	8"/200mm Euro-Cal IV El 12"/300mm Euro-Cal IV E CR2032 Battery		±.001"/.02mm ±.0015"/.03mm	136.50 175.10 5.70	95.00 122.00
XTRA-F	RANGE [®] Elec	ctronic (
			• Pre offs • 100-312-0 • Res • Incl • Incl • .50	Id feature eset mode now set for inside ja sizes feature fi nt screw solution: .0005 h/metric conve ludes molded o 0" internal mea	ws ne adjust- "/.01mm rsion case
					rowler SPC
	NE	W Shop-Harden			

14

Fowler-Sylvac Ultralight IV Electronic Calipers

The NEW Fowler-Sylvac Ultralight IV, new design, new features, built-in Bluetooth transmitter. Discover our amazing NEW Ultralight long range calipers.



- Built-in Bluetooth
- New reinforced frame
- XXL display with .79"/20mm high digits

∬∥4

1

- Increased accuracy
 Lengthened jaws 7.9"/200mm
 New system for internal measurement
- Protected to IP67
- Moveable left jaw
 Stainless steel titanium coated jaws
- Hold feature
- Preset function
- Min/Max functions
- Tolerance mode
- Internal and external measurement indicator
- New twin guided main beam

Specifications	54-110-512-0	54-110-524-0	54-110-540-0	54-110-560-0	54-110-580-0
Measuring Range	0-15"/0-400mm	0-24"/0-600mm	0-40"/0-1000mm	0-60"/0-1500mm	0-80"/0-2000mm
Maximum Error	30µm/0.0012"	40µm/0.0016"	50µm/0.002"	90µm/0.0035"	120µm/0.0048"
Repeatability	20µm/0.0008"				30µm/0.0012"
Measuring Force			5 - 10	N	
Connection			Bluetooth Smart/P	roxi RS232 or - U	SB
Protection Rating			IP67 (Electronie	c Module)	
Preset Max.	±9999.99 mm / ±399.9995 IN				
Weight	1.5 kg	1.6 kg	1.9 kg	2.3 kg	2.6 kg
Weight	1.5 kg	1.6 kg	1.9 kg	2.3 kg	2.6 kg

Order No.	Description	List Price	Sale Price
54-110-512-0	NEW 0-15"/0-400mm Ultralight IV	\$2086.50	\$1807.70
54-110-524-0	NEW 0-24"/0-600mm Ultralight IV	2434.30	2108.40
54-110-540-0	NEW 0-40"/0-1000mm Ultralight IV	2801.60	2521.40
54-110-560-0	NEW 0-60"/0-1500mm Ultralight IV	4212.70	3791.40
54-110-580-0	NEW 0-80"/0-2000mm Ultralight IV	5804.10	5223.10



NEW





NARRANI

/olume 15. 3

Snap-Cal

Fowler's Inch, Metric & Fraction reading Snap Caliper is ideal for measuring a wide range of materials from metal, plastics and glass to small wires, fibers and paper.

INCH • METRIC • FRACTION

- Range: 0-1.25"/31.5mm
- Resolution: .0005"/.01mm
- (Fractions in 1/64th increments).
- Spring-loaded travel.
- Wide faced flat jaw for easy positioning.
- Dimensions of fixed jaw: .470" x .900"
- Accuracy: ±.001"/.02mm
- Hardened stainless steel construction.
- Direct inch/metric/fraction conversion.
- Measuring speed of 60"/second.
- Large, high contrast LCD display
- Hanging loop included for attachment to belt or chain.

Order No.	Bange	List Price	Sale Price
Order No.	naliye	List Price	Sale Price
54-550-000-1	Snap-Cal	\$134.10	\$102.00
54-100-350-0	CR2032 Battery	5.70	

Save

over **2**(

OF

HOLD

ZERO

TRA-VALUE Internal & External Electronic Caliper Gages



- Large LCD display
- Reading: 0.001"/0.01mm/1/64ths
- Accuracy: 0.004"
- Includes 1/8" ball contact, cone point and a 1mm spline point

Fowler SNAP-CAL

13485

Leather Hollister Included!

- · Battery: CR2032
- Three interchangeable points
- · Battery life: approximately 1 year
- M2.5 contact point thread

INCH • METRIC • FRACTION

	UFF			
Order No.	Description	Range	List Price	Sale Price
54-554-830-0	Xtra-Valie Digital Thickness Gage	0-1"/25mm	\$51.40	\$38.00

16

Prices & Specifications are subject to change without notice.

HOLD

Fowler

ON/ZERO

mm/in/F

Small Hole Gage Set

Fowler's Small Hole Gage Set offers those in the metal working industry a tool for gaging deep and shallow holes, slots, etc. that are difficult to measure.

- Knurled knob at the end of the handle is used for size adjustment
- Hole size is obtained by measuring over the contact points with a micrometer.
- The gaging surface is a full-round with a flat bottom. This permits use in the smallest of shallow holes, slots and grooves, etc.
- Gaging surface is fully hardened to ensure long tool life
 Extra long for gaging deep and shallow holes, slots and sim
- Extra long for gaging deep and shallow holes, slots and similar work.
- The complete set of four gages covers a range of 0.125" 0.500"
- Includes fitted vinyl case

Order No. Description List Price Range Sale Price 52-472-104-0 Small Hole Gage Set (set of four) 0.125" - 0.500 \$81.40 \$74.50 **Telescoping Gage Sets** Another great tool for easy and accurate measurements. Under spring tension, the plungers of the gage expand from the center to the size of the hole being measured and are then locked in place using the knurled knob. Final hole size is obtained by measuring over the contacts with a micrometer or vernier caliper. Contact points are constructed of hardened tool steel, precision ground. Double action rigid handle with selfcentering feature for quick checking of inside measurements. Constant spring tension for uniform feel. Covers a measuring range of 5/16" to 6" with measurable depths of 4" to 5". Includes fitted vinyl case. 52-470-006-0 Order No. Description Range List Price Sale Price 52-470-006-0 6" Telescoping Gage Set (set of six) \$101.80 5/16" - 6 \$62.00 5/16" - 6" 52-470-007-0 12" Telescoping Gage Set (set of six) 122.60 \$75.00 **Titanium Coated** Telescoping Gage Set Another great tool for easy and accurate measurements. Under spring tension, the plungers of the gage expand from the center to the size of the hole being

expand from the center to the size of the nole being measured and are then locked in place using the knurled knob. Final hole size is obtained by measuring over the contacts with a micrometer or vernier caliper.

- Contact points are constructed of hardened tool steel, precision ground. Features titanium coated points for consistent accuracy and increased durability.
- Double action rigid handle with self-centering feature for quick checking of inside measurements.
- Constant spring tension for uniform feel.
- Covers a measuring range of 5/16" to 6" with measurable depths of 4" to 5".
- Includes fitted vinyl case.

Order No.	Description	Range	List Price	Sale Price
52-470-000-0	Titanium coated Telescoping Gage Set (set of six)	5/16" - 6"	\$113.20	\$79.00

Prices & Specifications are subject to change without notice.

17

lume .

Inside Micrometers

With Fowler Inside Micrometers you are assured of smooth operation and stabilized uniform accuracy. The frame is specially designed to enable the micrometer to provide extremely accurate small internal measurements.



Inside Micrometers

Fowler extension rod type Inside Micrometers have a wide measuring range - any one single micrometer can replace many bar type inside micrometers.



- · Each set consists of an inside micrometer head and a series of fully hardened and lapped extension rods of different lengths all with carbide measuring faces
- Anvil and spindle are hardened and precison ground with microlap finish on ends
- Spindle thread hardened, ground and lapped
- Microfine graduations on satin chrome
- · Positive locking nut on spindle

- · It is recommended that the inside micrometer with extensions be calibrated by a micrometer or ring gage
- Coiled spring pressure contact type rods are each marked with appropriate length
- Accuracy = 0.00005" x (3 + L"/2)
- Meets or exceeds Federal accuracy specs.
- Reference standard included with set
- · Includes a wrench and a case

Order No.	Range	Graduation	List Price	Sale Price
52-243-026-1	2" - 6"	0.001"	\$120.00	\$96.00
52-243-212-1	2" - 12"	0.001"	148.20	118.00
52-243-220-1	2" - 20"	0.001"	192.10	153.00
52-243-240-1	2" - 40"	0.001"	508.10	406.00
52-243-260-1	2" - 60"	0.001"	914.40	731.00
52-243-480-1	4" - 80"	0.001"	1071.20	856.00
52-243-512-1	2" - 120"	0.001"	2339.50	1871.00





Ultra-Cal III Electronic Depth Gage

Improved electronics with Direct RS232 Output. Available in two styles, these computerized measuring tools combine the advantages of Fowler's "Ultra-Cal III" Swiss patented measuring system with the rugged design of a full 12" capacity depth gage. Together they replace conventional vernier and dial depth gages and depth micrometers.

	NEW!	an LCD d inch/metr and the S glass sca Model No Features shoulders	except for the end isplay to .0005" (.1 ic conversion, incr ylvac non-contact les, racks, etc.). 5.54-130-012-0: a "hook" style end s, recesses, measing th of leg: .584".	01mm) reso remental floa reasuring I. Ideal for t	lution, direct ating zero, system (no hru-holes,
	Save	Features	54-135-012-0: a standard style e aging, blind holes		all hole entry,
	ever 20%	 Base ler .637"; b Low dra vironme of contin with use 	tions of Both Mo ngth: 6"; base widt eam thickness: .1 in, high efficiency ntally safe for disg huous on-time. Lift of on/off switch. cludes battery & d	th: .300"; be 20". lithium wafe bosal) offers fe extended	er battery (en- 4500 hours 2—3 years
54-130-012-0	54-135-012-0		OPTO INTERFACE	Mad GERN	
Order No.	Description	Range	Resolution	List Price	Sale Price
54-130-012-0 54-135-012-0	NEW Depth Gage with Hook NEW Depth Gage with standard	0-12"/300mm 0-12"/300mm	0.0005"/0.01mm 0.0005"/0.01mm	\$985.70 887.10	\$785.00 699.00

20





- Satin chrome finish
- Base surface hardened, ground
 & lapped
- Ratchet thimble
- Locking clamp
- .001" Graduation
- Rod diameter: .176"
- · Includes shop-hardened case.

52-225-226-0

Order No.	Range	Graduation	Base	List Price	Sale Price
52-225-110-0	0-4"	.001"	2.5"	\$116.00	\$102.80
52-225-112-0	0-6"	.001"	2.5"	143.60	126.30
52-225-114-0	0-4"	.001"	4"	125.30	110.20
52-225-116-0	0-6"	.001"	4"	146.80	131.00

Digit Counter Depth Micrometers

· Easy-to-read digit counter

- · Microfine .001" graduations
- 4" base constructed of tool steel, hardened and ground
- Satin chrome finish
- Ratchet thimble
- Locking clamp
- · Rod diameter: .176"
- · Includes wrench and fitted case

Order No.	Range	Graduation	Base	List Price	Sale Price
52-225-176-0	0-6"	.001"	2.5"	\$155.20	\$136.00
52-225-226-0	0-6"	.001"	4"	160.50	144.20





Prices & Specifications are subject to change without notice.





Order No.	Description	Graduations	Dial Diameter	List Price	Sale Price
52-562-004-0	Vertical X-Test Indicator	.0005"	1-1/2"	\$132.60	\$113.20
52-562-005-0	Vertical X-Test Indicator	.0005"	1"	132.60	113.20
52-562-006-0	Vertical X-Test Indicator	.001"	1"	132.60	113.20

Statest Indicator & Construction of the second of the s

Order No.	Description	Graduations	List Price	Sale Price
52-562-100-0	52-562-001 w/accessories	.0005"	\$177.80	\$159.00
52-562-110-0	52-562-002 w/accessories	.0005"	177.80	159.00
52-562-120-0	52-562-003 w/accessories	.001"	177.80	159.00

Prices & Specifications are subject to change without notice.

me .

ပာ ----

Test Indicators

All Fowler Test Indicators include bi-directional constant clockwise rotation, automatic reversal, three dovetail mountings, jeweled movement, two dovetail clamps and a molded case.



Order No.	Face Color	Total Range	Dial Reading	Graduation	Dial Diameter	Point Length	List Price	Sale Price
52-562-774-0	white	.030"	0-15-0	.001"	1"	1/2"	\$108.50	\$62.50
52-562-778-0	black	.030"	0-15-0	.0005"	1"	1/2"	115.30	67.50
52-562-775-0	white	.030"	0-15-0	.0005"	1"	1/2"	115.30	67.50
52-562-776-0	white	.030"	0-15-0	.0005"	1-1/2"	1/2"	120.60	74.00
52-562-780-0	black	.030"	0-15-0	.0005"	1-1/2"	1/2"	120.60	74.00



Order	Face	Total	Dial		Dial	Point	List	Sale
No.	Color	Range	Reading	Graduation	Diameter	Length	Price	Price
52-563-770-0	white	.008"	0-4-0	.0001"	1"	1/2"	\$ <mark>115.30</mark>	\$93.10
52-563-771-0	black	.008"	0-4-0	.0001"	1"	1/2"	115.30	93.10
52-563-777-0	white	.008"	0-4-0	.0001"	1-1/2"	1/2"	115.30	93.10
52-563-772-0	black	.008"	0-4-0	.0001"	1-1/2"	1/2"	115.30	93.10



Order	Face	Total	Dial		Dial	Point	List	Sale
No.	Color	Range	Reading	Graduation	Diameter	Length	Price	Price
52-562-781-0	white	.020"	0-10-0	.0005"	1"	1-7/16"	\$118.80	\$89.80
52-562-782-0	black	.020"	0-10-0	.0005"	1"	1-7/16"	118.80	89.80
52-562-783-0	white	.020"	0-10-0	.0005"	1-1/2"	1-7/16"	118.80	89.80
52-562-784-0	black	.020"	0-10-0	.0005"	1-1/2"	1-7/16"	118.80	89.80

FOWIER TOOL-A-THON

24



Order No.	Range	Graduation	Reading	Balanced Reading	Dial Color	List Price	Sale Price
52-520-110-1	NEW 1"	0.001"	0-100	_	Black Face	\$85.00	\$68.00
52-520-110-2	NEW 1"	0.001"	0-100	-	White Face	85.00	68.00
52-520-105-0	NEW 0.500"	0.001"	0-100	0-50-0	White Face	80.40	64.00
52-520-120-0	NEW 2"	0.001"	0-100	0-50-0	White Face	131.50	104.00
52-520-129-0	NEW 1"	0.0005"	0-50	0-25-0	White Face	102.80	81.00
52-520-135-0	NEW .05"	0.0001"	0-10	0-5-0	White Face	147.30	117.00
52-520-125-0	NEW 0.250"	0.0005"	0-50	0-25-0	White Face	112.20	89.00
52-520-127-0	NEW 0.250"	0.0005"	_	0-25-0	White Face	105.40	84.00
52-520-128-0	NEW 1"	0.0005"	0-50	-	White Face	123.50	98.00
52-520-300-0	NEW 10mm	0.01mm	0-100	0-50-0	White Face	95.20	76.00
52-520-400-0	NEW 5mm	0.002mm	_	0-10-0	White Face	153.00	122.00
52-520-500-0	NEW 25mm	0.01mm	0-100	0-50-0	White Face	129.40	103.00

Test Indicator Set with Certificate of Calibration

0.03 Inch

na : 0.0005 Inch

Tested in accordance to : ANSI B89.1.10M-1987

CERTIFICATE OF CALIBRATION

-0.0004

Graduation : 0 - 15 - 0

15

-0.0003

Gauge Serial No : F 6065

Certificate No. : 7364

-0.0002

-0.0003

Test Indicator:

- Auto-reverse.
- · Jeweled movement.
- Range: .030"
- Graduation: .0005"
- Dial Reading: 0-15-0
- Dial Diameter: 1.125"
- Point length: .400"
- Carbide contact points

Set Also Includes:

- .080" & .040" contact points
- Universal clamp
- Height gage attachment
- 3/8" & 1/4" dovetail clamps
- Test certificate
- All in a fitted molded case.

Order No.	Range	Dial Reading	Graduation	Dial Diameter	Point Length	List Price	Sale Price
52-562-999-0	0.030"	0-15-0	0.0005"	1.125"	0. <mark>400"</mark>	\$115.50	\$105.60

Volume 15.3

25



2-1/4" dial face
Lugback and 3/8" stem mountings

- Resolution .0005"/.01mm 54-520-260-0
- Tolerance indicators
- Absolute/incremental reading
- Floating zero
- Carbide tipped point

Low Cost, High Quality, Multi-Function Indicators

54-520-250-0

Carbide-tipped point!

Order No.	Description	List Price	Sale Price
54-520-250-0	1"/25mm Indi-X Blue Electronic Indicator	\$96.80	\$72.00
54-520-260-0	1"/25mm/64ths Indi-X Blue Inch-Metric-Fraction Electronic Indicator	99.10	73.50
54-520-255-0	.5"/12.5mm Indi-X Blue Electronic Indicator	89.90	63.50

A-THOA

BEST SELLE



Fowler-Bowers Holematic XTH3 Pistol Grips Sets

Fowler-Bowers XTH3 Holematic Pistol Grip bore gages offer extended travel with fixed anvils. The pistol grip handle incorporates a constant measuring force to eliminate operator "feel".

NEW Larger Display! NEW Ergonomic Design! NEW Four Presets! NOW Available with <u>Bluetooth!</u>

- · Larger (10mm) easier to read swivel display
- Self centering heads
- · USB connectivity, Bluetooth is available
- Four preset memories
- Fixed anvils
- Resolution: .00005" /.001mm
- Range .080"-12" (2-300mm)
- To reduce hand fatigue, the travel of the Holematic trigger is adjustable for minimum over travel
- Tungsten carbide measuring faces on all 3-point heads from .5" (12.5mm) and up.
- Heads with special anvils available for threads, splines, slots, etc.
- · Sizes over .500" (12.5mm) feature blind bore capability
- Setting rings included in all sets
- Includes UKAS certificates for all pistol grip, heads and rings
- Special anvils available
- Contact the Fowler Technical Department for special anvil applications.



TOOL-A-THON

Available with BLUETOOTH! Contact the Fowler Sales Department for more information.

Complete Range Sets

	Complete hange	5615			
-	Order No.	Range	Includes	List Price	Sale Price
	54-567-009-0	.080"250" (2-6mm)	5 heads, 1 handle, 3 rings	\$5739.00	\$4878.15
	54-567-010-0	.250"375" (6-10mm)	2 heads, 1 handle, 1 ring	2154.00	1830.90
	54-567-020-0	.375"750" (10-20mm)	3 heads, 1 handle, 2 rings	2547.00	2164.95
	54-567-050-0	.750"-2" (20-50mm)	3 heads, 1 handle, 2 rings	3334.00	2833.90
	54-567-100-0	2-4" (50-100mm)	3 heads, 1 handle, 2 rings	3730.00	3170.50
-	54-567-105-0	4-6" (100-150mm)	2 heads, 1 handle, 1 ring	3334.00	2833.90
	54-567-110-0	6-8" (150-200mm)	2 heads, 1 handle, 1 ring	4453.00	3785.05
	54-567-200-0	4-8" (100-200mm)	4 heads, 1 handle, 2 rings	7141.00	6069.85
	54-567-210-0	.750"-4" (20-100mm)	6 heads, 1 handle, 4 rings	5527.00	4697.95
5	54-567-620-0	.250"750" (6-20mm)	5 heads, 1 handle, 3 rings	3066.00	2606.10
	Connectivity Kits	· · · ·	· · · ·		
	Order No.	Description			
	54-115-526-0	Proximity cable with USB conne	ection	133.40	
	54-115-527-0	Proximity cable with serial conn	ection	133.40	
62	54-100-350-0	CR2032 Battery		5.70	







54-567-020-0

Fowler-Bowers XTD3 Electronic Holemike Sets

Fowler-Bowers XTD3 Electronic Holemike bore gages offer extended travel with fixed anvils. The micrometer style ratchet system ensures a constant measuring force to eliminate operator "feel".

NEW!



Complete Range Sets

complete nange t	5015				
Order No.	Range	Includes		List Price	Sale Price
54-367-000-0	.080"250" (2-6mm)	5 heads, 1 handle, 3 ring	S	\$5739.00	\$4878.15
54-367-010-0	.250"375" (6-10mm)	2 heads, 1 handle, 1 ring		2154.00	1830.90
54-367-020-0	.375"—.750" (10—20mm)	3 heads, 1 handle, 2 ring	s	2547.00	2164.95
54-367-050-0	.750"-2" (20-50mm)	3 heads, 1 handle, 2 ring	s	3334.00	2833.90
54-367-100-0	2-4" (50-100mm)	3 heads, 1 handle, 2 ring	s	3730.00	3170.50
54-367-105-0	4-6" (100-150mm)	2 heads, 1 handle, 1 ring		3334.00	2833.90
54-364-110-0	6-8" (150-200mm)	2 heads, 1 handle, 1 ring		4453.00	3785.05
54-367-200-0	4-8" (100-200mm)	4 heads, 1 handle, 2 ring	s	7141.00	6069.85
Connectivity Kits					
Order No.	Description				
54-115-526-0	Proximity cable with USB conne	ection		133.40	
54-115-527-0	Proximity cable with serial conn	ection		133.40	
54-100-350-0	CR2032 Battery			5.70	

TOOL-A-THON

Volume 15.3

We are so confident that these Fowler-Sylvac products are the most accurate, most dependable, best made products you can buy, we are extending the warranty to last a lifetime!

Quality, accuracy, dependability, world-class customer service and now a real Lifetime Warranty!

NO Gimmicks NO Hurdles NO NONSENSE

Mark VI Electronic Indicators



54-530-555-0

0-1.00"/25mm

Prices & Specifications are subject to change without notice.

0.00005"/.001mm

664.40

530.00

0.00016"/0.004mm

ULTRATAST TEST INDICATORS Horizontal Test Indicators

- · Box-type housing opens on one side only.
- · Bottom and side walls are one piece construction which encloses and protects the movement from shocks and damage.
- Self-contained movement
- · Jeweled movement bearings, precision gears and pinions for maximum sensitivity and accuracy
- Satin-chrome finish is corrosion proof
- Stylus: ball diameter .080"/2mm
- · Swivel range 220° on all models
- Includes 1/4" & 5/16" Dovetail clamps

Order No.	Reading	Measiuring Range	Dial Diameter	Stylus Length	Measuring Force
52-568-005-0	.0005"	±.015"	1.083"	.453"	0.15N
52-568-010-0	.0005"	±.015"	1.50"	.453"	0.15N
52-568-015-0	.0001"	±.004"	1.50"	.453"	0.15N
52-568-022-0	.0005"	±.015"	1.083"	1.417"	0.07N

OVERSTOCK SPECIA

Order No. 52-568-005-0 52-568-010-0 52-568-015-0 52-568-022-0

Description	List Price	S
UltraTast Horizontal Test Indicator	\$124.60	
UltraTast Horizontal Test Indicator	141.60	
UltraTast Horizontal Test Indicator	181.30	
UltraTast Horizontal Test Indicator	202.80	

Sale Price \$45.00 45.00 45.00 45.00

52-568-005-0

Made in GERMANY

TOOL-A-THON

.000

15

OLDXTEC Holding Systems

- All accept 3/8" indicators
- · Mag base and HOLD-TEC with fine adjust also accepts 8mm indicators
- · All have dovetail clamps for test indicators

8mm stem Save 0%

- · Mag base features 2 fine adjusts making it a 6-Axis Mag Base
- · HOLD-TEC can be mounted in drill chucks, collets, dial gage stands with 8mm mount diameter to make a quick transfer stand
- Mag base has 180 lb. pull
- · Adjust to any position
- Powerful On/Off mag base
- Central locking system



Features **Double Fine Adjust**

52-565-036-0 (Indicator not included) 52-585-085-0

(Indicator not included)

MACHINIST GRADE!

For MAXIMUM Precision

Volume 15 6

52-565-038-0 (Indicator not included)

Order No.	Description	List Price	Sale Price
52-585-085-0	HOLD-Tec Mag Base with Double Fine Adjust	\$151.70	\$120.00
52-565-036-0	HOLD-Tec without Fine Adjust	85.20	68.00
52-565-038-0	HOLD-Tec with Fine Adjust	92.60	74.00

Prices & Specifications are subject to change without notice.

CHROME FLEX MAG SET with INDI-X IIII Electronic Indicator or AGD Black face Indicator



Order No.	Description	List Price	Sale Price
54-585-100-0	Chrome Flex Mag and Indi-X Blue Electronic Indicator Set	\$237.90	\$165.00
52-585-500-0	Chrome Flex Mag and AGD Black Face Indicator Set	178.40	123.00

X-PROOF Water Resistant Indicator Set BEST VALUE! **IP54 Shockproof indicator available!** Magnetic Base (52-585-010-0): WLER HIGH · Fine adjustment Base dimensions: 2" x 2-11/32" x 1-13/16" Mounts test indicators with 1/4" post 85 lb. pull · On-Off lever release magnet · V-base for placing on round surfaces X -Proof Indicator (52-520-450-0): Travel: 1' · Reading: .001" Continuous reading: 0-100 Tolerance markers · AGD Group 2, 2-1/4" dia. · Lugback and carbide point Robust, shockproof design Rubber bellows on stem · O-ring seal on safety cap O-ring protection for bezel and rotating dial Sealed back plate All in a shop-hardened case.

Order No.	Description	List Pice	Sale Price
52-585-155-0	X-Proof Water Resistant Indicator Set	\$79.40	\$66.50



<section-header> Dial Bore Gage Sets with Carbide Anvils Carbide anvils Easy-to-read Economical Graduation: .005" Chrome plated handle Insulated grip Includes extension holder and fitted case

Order No.	Description	Range	List Price	Sale Price
52-646-100-0	Dial Bore Gage Set	.7-1.5"	\$143.30	\$106.30
52-646-300-0	Dial Bore Gage Set	2-6"	118.40	106.30

	r 1.4" to 6" or 35r e Gage Setswith Ca		DEST SEL	
XTENI	DER Industry's two most ranges combin		POWLER HIGH	PRESS
Carbide Anvill. • Easy-to-read • Economical • Graduation . 0 • Insulated grip • 1.4" to 6" rang • Chrome platec • Includes exten and fitted case	005" or .01mm e or 35 to 160mm handle sion holder	52-646-40	0-0	
Order No.	Description	Graduation	List Price	Sale Price

Order No.	Description	Graduation	List Price	Sale Price
52-646-400-0	Inch X-Tender Bore Gage Set	0.0005"	\$180.00	\$128.30
52-646-500-0	Inch X-Tender Bore Gage Set	0.0001"	225.00	183.30
52-646-220-0	Metric X-Tender Bore Gage Set	0.01mm	198.90	138.50
In the second second second second	the strange of the second s			and the second second

Extender-E Electronic 1.4" to 6" Dial Bore Gage Set Industry's two most popular bore gage ranges combined in one easy-to-use ELECTRONIC set!

All the same benefits included in the X-Tender Dial Bore Gage are now available with an electronic indicator providing inch/metric reading capability. Preset size of master for absolute reading and minimum hold feature to lock on the bore size as the gage is rocked in the part to be measured.



Prices & Specifications are subject to change without notice.



mini-MAG Protractor





Fowler Digi-Pro Electronic Protractors

The Digi-Pro electronic protractor includes embedded magnets for unique measurement areas. On/Off, Zero, Hold and Reverse feature to invert the display for easier reading in certain situations.

- · Embedded 25 lb. pull magnets
- Full, 360° measuring range
- Accuracy: ±.2°
- Repeatability: ±.05°
- Resolution: .05°
- Invertible display feature
- Voltage: Standard 3V lithium battery





-

USE THE DIGI-PRO TO MAKE FAST AND ACCURATE ANGULAR MEASUREMENTS!

Order No.	Description	List Price	Sale Price
54-440-740-1	4" Digi-Pro Electronic Protractor	\$85.00	\$64.70
54-440-775-1	12" Digi-Pro Electronic Protractor	101.90	69.80
54-100-350-0	CR2032 Battery	5.70	

Save

36



V-Block Set

The Fowler Universal-type V-Block is a precise tool used for layout work in the tool room and has the capability of holding square or round workpieces with greater accuracy

- Two clamps, with screw hole at 90 degrees for positive clamping of work, are included.
- Clamping capacity=2"(50mm.)
- V-Blocks are constructed with stepped grooves which allow the clamps to be inserted without protrusion, thus allowing V-Blocks to be used on base, ends or sides.
- Hardened steel. All sides of V-Blocks precision ground parallel and square within .0004".
- Matched pair of V-Blocks are perfectly aligned with 90 degree V-grooves ground central and parallel to the sides and base.

NEW Shop-Hardened Case!

	the state of the s				
Order No.	Height	Length	Width	List Price	Sale Price
52-475-555-0	2"	2-3/4"	2"	\$229.80	\$165.50

V-Block Set

- Parallel and square within .0003".
- · Dimensions: L 1-3/8" x W 1-3/8" x H 1-3/16"
- · Reversible swing-away clamps
- Ø capacity: .030" to 1.285"
- Versatile clamp plus unique offset hole pattern in top of blocks, offers a large variety of clamping possibilities.

Order No.	Description	List Price	Sale Price
52-475-001-1	NEW V-Block Set	\$50.80	\$33.00

NEW!



2 each @:

- Dimensions: 1-1/2" L x 1-1/4" W x 1-1/4" H.
- Work capacity: Approximately 1"
- 2 each @:
- Dimensions: 2" L x 1-1/2" W x 1-1/2" H.
- Work capacity: 1-1/2"

All feature:

- Surfaces are square and parallel within .0005"
- V-grooves are square and parallel with all surfaces within .0005"
- Corresponding dimensions for each pair are alike within .0005"
- · All enclosed in shop-hardened case



Save

Order No.	Description	List Price	Sale Price
52-475-500-0	X-Blox V-Block Set	\$113.90	\$87.60

1-2-3 & 2-4-6 Blocks	Steel 1-2-3 Blocks	
52-432-246-0 52-432-246-0 • 23 holes for easy clamping • Sold in pairs	Save over 40%	. <u>ow</u> ler
Useful in layout & grinding work Accuracy: ±.0002"/1" Matched accuracy: ±.0002" Order No. Description List Price Sale Price 52-439-031-0 1-2-3 Blocks \$87.10	Tolerance: .0001" (squareness per inch) Dimensions: 1" x 2" x 3" Hardened to 58-60 Rockwell C. Matched accuracy within ±.0002" Order No. List Price Sale Price De 100 000	тос
52:439:246-0 2:4-6 Blocks 205.50 154.50 Premium 1-2-3 Block Set Optimization of the set of the s	52-439-001-0 \$133.20 \$75.20 Start and the second secon	FOOL-A-THON
52-439-032-0 \$79.90 \$67.00 1/8" Parallel Set Image: Set of the set	 53-439-101-0 \$288.40 \$225.00 Adjustable Parallels Figure 1 and the stress of the stress	Volume 15.3
Order No. List Price Sale Price 52-437-000-0 \$218.10 \$165.00	Order No. List Price Sale Price 52-437-006-0 \$132.00 \$115.00	15.3

Combination Square

- Blades are chrome plated, fully hardened and tempered,
- Square head has level and scriber point
- Double indexed protractor is graduated 180° in both directions
- 52-370-012-0 graduated in 8ths, 16ths, 32nds and 64ths
- 52-378-006-0 graduated in 30nds, 64ths, 50ths and 100ths



Order No.	Description	List Price	Sale Price
52-370-012-0	Square, Protractor and Center Head with 12" blade	\$177.50	\$133.70
52-378-006-0	2 piece combination square, includes square head and 6" blade	72.60	60.80
Protract	ors		

NEW!

Semi-Circular Head - 52-450-005-0

- Measures angles from 0-180 degrees.
- · Used for drawing radial lines at any angle.
- Measures 3-5/16" in diameter and features a lock nut and 6" arm with knurled thumb lock nut.

Rectangular Head - 52-450-010-0

- · Measures angles from 0-180 degrees.
- · Used to transfer angles and to set bevels.
- 6" arm with knurled thumb lock nut.
- · Made of chrome steel with satin finish.
- Measures 3-5/16" x 2". Rectangular head provides four working edges. Blade secured firmly at any angle by a lock joint and knurled nut.

52-450-005-0

Save

over 25%

52-450-010-0

Order No.	Description	List Price	Sale Price
52-450-005-0	NEW Protractor — Semi-Circular Head	\$44.00	\$32.00
52-450-010-0	Protractor — Rectangular Head	50.80	34.00

Edge Finder Set

Contains:

- 3/8" x .200" Edge Finder
- 1/2" x .200" Edge Finder
- 1/2" x .200" Combo Edge Finder
- 1/2" x .500" Edge Finder
 - · Complete in fitted case.





54-575-600-0

54-575-625-0

Order No.	Description	List Price	Sale Price
52-575-125-0	Edge Finder Set	\$47.10	\$37.50
the second second second second second			and the second

Electronic Edge Finders

- Six equally spaced light ports provide visibility at any angle
- Made in the USA
- Edge finder lights instantly when stylus touches work edge
- Repeatability: .0002"
- Works on any conductive metal

🕒 Save 🚄	
15% or 1	
1570	
More!	

	-	-	
SOL-A-THON			
SOL THE	RI		
EST SELLE	N.	-	-

54-5	75	650	0
54-5	13-	050	-0

Along with light indication, model #54-575-650-0 emits an audible "beep" at time of c	ontact.
---	---------

Order No.	Stylus	Shank	Audible	Battery	List Price	Sale Price
54-575-600-0	.200"	1/2"	NO	12 volt	\$30.80	\$23.50
54-575-625-0	.200"	1/2"	NO	12 volt	108.60	90.60
54-575-650-0	.400"	3/4"	YES	12 volt	108.60	90.60

RULES

- EZ-Read Black Face Rules
- Hardened stainless steel
- White easy-to-read microfine graduations against a black, non-glare finish

ана политически политически политически политически политически политически политически политически политически заказа такжа политически политически политически политически политически политически политически политически поли политически политически политически политически политически политически политически политически политически поли политически политически политически политически политически политически политически политически политически поли политически политичес политически политически политически политически политически политически политически политически политически поли политически политически политически политически политически политически политически политически политически поли

52-330-006-0

GRADUATIONS

4R: 8ths, 16ths, 32nds, 64ths

5R: 32nds, 64ths, 10ths, 100ths

1 2 FORM 3 AMERICA 4 FRANCE 5

52-297-006-0

- Satin Chrome Rules
- Tempered steel
- Non-glare
- · Sharp, easy-to-read
- microfine graduations

SAAA **Golden Rules** · Titanium coated for superior wear resistance

1 2 3 мае но ца 4 темено 5 « то 32 1 2 3 мае но ца 4 темено 5 « то 32 1 4 0 ⁵ ю м.я. 4 в 0 ⁵ ю м.я.

Save over 10%

- Non-glare finish=RC80
- Scratch resistant microfine graduations with excellent clarity and contrast

52-299-006-0

RIGID STEEL P	RULES				
Order No.	Finish	Size	Reading	List Price	Sale Price
52-330-006-0	Satin Chrome	6"	4R	\$10.90	\$8.90
52-337-006-0	Black	6"	4R	9.20	6.40
52-339-006-0	Golden	6"	4R	22.70	17.80
52-330-012-0	Satin Chrome	12"	4R	18.90	15.00
52-337-012-0	Black	12"	4R	18.90	11.00
52-339-012-0	Golden	12"	4R	43.50	34.80
52-340-006-0	Satin Chrome	6"	5R	10.50	7.80
52-347-006-0	Black	6"	5R	9.20	6.40
52-349-006-0	Golden	6"	5R	22.70	17.80
52-340-012-0	Satin Chrome	12"	5R	17.20	15.00
52-347-012-0	Black	12"	5R	18.90	11.30
52-349-012-0	Golden	12"	5R	43.50	34.80

FLEXIBLE STEEL RULES

Order No.	Finish	Size	Reading	List Price	Sale Price
52-295-006-0	Satin Chrome	6"	4R	\$10.50	\$7.30
52-297-006-0	Black	6"	4R	8.60	5.90
52-299-006-0	Golden	6"	4R	22.30	18.20
52-295-012-0	Satin Chrome	12"	4R	16.10	13.40
52-297-012-0	Black	12"	4R	13.20	10.20
52-299-012-0	Golden	12"	4R	40.00	32.10
52-300-006-0	Satin Chrome	6"	5R	10.80	7.30
52-307-006-0	Black	6"	5R	8.60	5.90
52-309-006-0	Golden	6"	5R	22.30	18.20
52-300-012-0	Satin Chrome	12"	5R	16.10	13.40
52-307-012-0	Black	12"	5R	13.20	10.20
52-309-012-0	Golden	12"	5R	40.00	32.10

6"/150mm Pocket Steel Rule

- Rounded edge prevents damage to shirt pocket
 Rule width: .470"
- Inch graduations are in 64ths

- · Metric scale is in 1mm increments
- · Rule thickness: .021"

			CR HIGH	
Order No.	Description	List Price	Sale Price	
52-380-100-0	6"/150mm Pocket Steel Rule	\$6.90	\$5.10	

Prices & Specifications are subject to change without notice.

Volume 15.3

4 15

BEST SELLER!

Thick	ness Ga	ges			ML
Each leaf of fine temper The exact the Steel case	f the thickness g red steel, harder	gage made of ned ked on each leaf		2	Save 0-40%
	ST SELLER!				
	BEST JELL B			0.05-1.00mm 29 BLATT	437
	WLER HIGH PRE	52-485-010-0		20 BAIL	
Order No.	Description				Sale Pric
52-485-006-0	.004", .005", .006	S", .007", .008", .009", .	Set: .0015", .002", .0025", .003 010", .011", .012", .013", .014", 021", .022", .023", .024" and .02		\$12.3
52-485-010-0	0.15mm, 0.20mm 0.50mm, 0.55mm	n, 0.25mm, 0.30mm, 0.	eaf Set: 0.05mm, 0.10mm, 35mm, 0.40mm, 0.45mm, 70mm, 0.75mm, 0.80mm, Length: 100mm.	\$18.00	\$10.3
Screw	Pitch C	Gages	Save		
	METRISCH MARE DE GEDMAN	a	TANAL		
Congrand of	7	AN COLOR	ACME SCREW PITCH GAGE		A
		use for internal and ex	ternal serew threads	Screw Pitch Gage 5	52-485-030-0
Locking devic Correct pitch Precisely grou Blades marke	e at each end to s is determined by m und and finished ed with thread size Pitch Gage (29° ar	ecure all blades for sto hatching blade teeth wi ngle)	rage or position th threads	Screw Pitch Gage 5	52-485-030-0
Locking devic Correct pitch Precisely grou Blades marke	e at each end to s is determined by n und and finished ad with thread size Pitch Gage (29° ar stainless steel. Eac	ecure all blades for sto natching blade teeth wi	rage or position th threads	Screw Pitch Gage 5	52-485-030-0
Locking devic Correct pitch Precisely grou Blades market Acme Screw F Made of fine s .03"/.8mm thi Order No.	e at each end to s is determined by n und and finished ad with thread size Pitch Gage (29° ar stainless steel. Eac	ecure all blades for sto hatching blade teeth wi ngle)	n long and		
Locking devic Correct pitch Precisely grou Blades marke Acme Screw F Made of fine s .03"/.8mm thi	e at each end to so is determined by m und and finished ed with thread size Pitch Gage (29° ar stainless steel. Eac ick	ecure all blades for sto natching blade teeth wi ngle) h blade is 3-1/2"/90mr Descriptior	n long and		Sale Pric
Locking devic Correct pitch Precisely grou Blades market Acme Screw F Made of fine s .03"/.8mm thi Order No. Inch Series 52-485-015-0 Metric Series	e at each end to s is determined by m und and finished ad with thread size Pitch Gage (29° ar stainless steel. Eac ick Screw Pitch (s	ecure all blades for sto natching blade teeth wi ngle) ch blade is 3-1/2"/90mr Description Gage with 30 blades: 4	n long and to 42 pitch standard V thread	List Price \$10.80	Sale Pric
Locking devic Correct pitch Precisely grou Blades marke Acme Screw F Made of fine s .03"/.8mm thi Order No. Inch Series 52-485-015-0	e at each end to s is determined by m und and finished ad with thread size Pitch Gage (29° ar stainless steel. Eac ick Screw Pitch (Screw Pitch (S	ecure all blades for sto natching blade teeth wi ngle) ch blade is 3-1/2"/90mr Description Gage with 30 blades: 4 Gage with 24 blades: 0	n long and to 42 pitch standard V thread	List Price \$10.80 10.80	Sale Pric \$8.2 8.2
Locking devic Correct pitch Precisely grov Blades marke Acme Screw P Made of fine s .03"/.8mm thi Order No. Inch Series 52-485-015-0 Metric Series 52-485-020-0 Acme Series	e at each end to s is determined by m und and finished ad with thread size Pitch Gage (29° ar stainless steel. Eac ick Screw Pitch (Screw Pitch (C Screw Pitch (Screw	ecure all blades for sto natching blade teeth wi ngle) ch blade is 3-1/2"/90mr Description Gage with 30 blades: 4 Gage with 24 blades: 0	n long and to 42 pitch standard V thread .25mm to 6.0mm ides (1, 1-1/3", 1-1/2", 1-3/4", 2,	List Price \$10.80 10.80	Sale Pric \$8.2 8.2
Locking devic Correct pitch Precisely grov Blades marke Acme Screw P Made of fine e .03"/.8mm thi Jorder No. Inch Series 52-485-015-0 Metric Series 52-485-020-0 Acme Series 52-485-030-0	e at each end to s is determined by m und and finished ad with thread size Pitch Gage (29° ar stainless steel. Eac ick Screw Pitch (0 Screw P	ecure all blades for sto natching blade teeth with the blade is 3-1/2"/90mr Description Gage with 30 blades: 4 Gage with 24 blades: 0 Pitch Gage with 16 bla	n long and to 42 pitch standard V thread .25mm to 6.0mm ides (1, 1-1/3", 1-1/2", 1-3/4", 2, %12 pitch)	List Price \$10.80 10.80	Sale Pric \$8.2 8.2
Locking devic Correct pitch Precisely grou Blades marke Arme Screw F Made of fine st. 03".8mm thi Order No. Inch Series 52-485-015-0 Metric Series 52-485-015-0 Metric Series 52-485-030-0 Thread Metric sixteen diffi Accuracy fc	e at each end to s is determined by n und and finished ad with thread size Pitch Gage (29° ar stainless steel. Eac ick Screw Pitch (0 Screw Pitch (0 Acme Screw 2-1/2", 3, 3-1/2 d Measu assuring Wires in erent sizes 0 or sizes, 0.18" thi	ecure all blades for sto natching blade teeth with the blade is 3-1/2"/90mr Description Bage with 30 blades: 4 Bage with 30 blades: 0 Pitch Gage with 16 bla (2", 4, 5, 6, 7, 8, 9, 10 8 Pitch Gage with 16 bla (2", 4, 5, 6, 7, 8, 9, 10 8 Clude 48 wires in rough .108" is	n long and to 42 pitch standard V thread .25mm to 6.0mm ides (1, 1-1/3", 1-1/2", 1-3/4", 2, %12 pitch)	List Price \$10.80 10.80	Sale Pric \$8.2 8.2
Locking devic Correct pitch Precisely group Blades marke Arme Screw F Made of fine 3: 03".8mm thi Order No. Inch Series 52-485-030-0 Acme Series 52-485-030-0 Acme Series 52-485-030-0 Thread Met sixteen diff Accuracy for Activen diff Accuracy for 1185" is with Measures a threads per Laminated	e at each end to s is determined by m und and finished ad with thread size Pitch Gage (29° ar stainless steel. Eac ick Screw Pitch (0° Screw Pitch (0° Screw Pitch (0° Acme Screw 2-1/2", 3, 3-1/ C MCEASI assuring Wires in erent sizes pr sizes. 018" thr -0004"; sizes. 1 hin +0 /0005" all U.S. 60° threat	ecure all blades for sto natching blade teeth with hgle) ch blade is 3-1/2"/90mr Description Bage with 30 blades: 4 Bage with 30 blades: 0 Pitch Gage with 16 bla (2", 4, 5, 6, 7, 8, 9, 10 8 Curring Wires clude 48 wires in rough .108" is 20" through	n long and to 42 pitch standard V thread .25mm to 6.0mm ides (1, 1-1/3", 1-1/2", 1-3/4", 2, %12 pitch)	List Price \$10.80 10.80	Sale Pric \$8.2 8.2
Locking devic Correct pitch Precisely group Blades marke Arme Screw F Made of fine 3: 03".8mm thi Order No. Inch Series 52-485-030-0 Acme Series 52-485-030-0 Acme Series 52-485-030-0 Thread Met sixteen diff Accuracy for Activen diff Accuracy for 1185" is with Measures a threads per Laminated	e at each end to s is determined by m und and finished ad with thread size Pitch Gage (29° ar stainless steel. Eac ick Screw Pitch (0 Screw Pitch (0 Screw Pitch (0 Screw Pitch (0 Acme Screw 2-1/2", 3, 3-1) d Measuring Wires in erent sizes or sizes .018" thr 0005" all U.S. 60° threat r inch conversion char	ecure all blades for sto natching blade teeth with the blade is 3-1/2"/90mr Description Gage with 30 blades: 4 Gage with 30 blades: 4 Gage with 24 blades: 0 Pitch Gage with 16 bla /2", 4, 5, 6, 7, 8, 9, 10 & Wiring Wire clude 48 wires in rough .108" is 20" through ads from 3-48	n long and to 42 pitch standard V thread .25mm to 6.0mm ides (1, 1-1/3", 1-1/2", 1-3/4", 2, %12 pitch)	List Price \$10.80 10.80	Sale Pric \$8.2 \$8.2 79.0
Locking devic Correct pitch Precisely group Blades marke Arme Screw F Made of fine 3: 03".8mm thi Order No. Inch Series 52-485-030-0 Acme Series 52-485-030-0 Acme Series 52-485-030-0 Thread Met sixteen diff Accuracy for Activen diff Accuracy for 1185" is with Measures a threads per Laminated	e at each end to s is determined by m und and finished ad with thread size Pitch Gage (29° ar stainless steel. Eac ick Screw Pitch (0 Screw Pitch (0 Screw Pitch (0 Acme Screw 2-1/2", 3, 3-1/ d Measu assuring Wires in erent sizes or sizes. 018" thr 0004"; sizes. 1 hin +0 /0005" all U.S. 60° threat conversion char ads is included	ecure all blades for sto natching blade teeth with the blade is 3-1/2"/90mr Description Gage with 30 blades: 4 Gage with 30 blades: 4 Gage with 24 blades: 0 Pitch Gage with 16 bla /2", 4, 5, 6, 7, 8, 9, 10 & Wiring Wire clude 48 wires in rough .108" is 20" through ads from 3-48	In long and to 42 pitch standard V thread .25mm to 6.0mm ades (1, 1-1/3", 1-1/2", 1-3/4", 2, k12 pitch) Set Save over 25%	List Price \$10.80 95.90	Sale Pric \$8.2 8.2



Stereo Zoom Microscopes are used in the electronics and precision machine industries for assembling and inspection of products. They are suitable for micrography and observation of fine structure of irregular bodies because of their high resolution and clear imaging within a broad field of view. They are also suitable for educational purposes in schools and hospitals and in agriculture, forestry, medical service, geology, archeology and biology fields.

Order No.	Description	List Price	Sale Price
53-640-778-0	NEW Deluxe Zoom Head with 10X eyepieces ONLY (for use with 53-640-740-0)	\$1074.00	\$590.00
53-640-740-0	NEW Universal Zoom Stand with top light for 53-640-778-0	496.16	309.00

Optical Comparator with Accessory Package



Includes: T-Slot V-Blocks & T-Slot Centers shown

The Fowler comparator is economically designed for basic comparative and absolute measurements and includes:

 10X Lens 12" 1 Quadrant protractor screen T-slot stage with 6" horizontal travel and 2.5" vertical travel. 1 pair of t-slot mounted V-blocks 	Save
 1 pair of t-slot mounted centers 2 Electronic AGD 2 Indicators: 1"/25mm capacity with .0005"/.01 resolution 	53-900-100-0

Order No.	Description	List Price	Sale Price
53-900-100-0	Optical Comparator with Accessory Package	\$-2475.00	\$1850.00
53-900-000-0	12" Basic Bench Top Optical Comparator	2286.40	1750.00

Prices & Specifications are subject to change without notice.

olume 15/

ີພ



TOOL-A-THON





FOWIER TOOL-A-THON

46



LHON



Reduced

· Small, compact size

ТΜ


- · 2 selectable parameters: Ra and Rz
- · Large LCD display
- · Meets ISO and DIN standards
- · N.I.S.T. traceable specimen included
- Uses 9 volt battery (aprox. 3000 measurements)
- · Includes fitted case

54-410-500-0

The X-Pro Portable Roughness Tester II can be used for many applications by selecting from a variety of accessories, including:

- · Stand with swivel
- · A variety of probes

For certain Applications, RS232 is available on certain models (contact the Fowler technica e information)



List Price

\$1693.80

1693.80

Sale Price

\$1499.00

\$1499.00

List Price

List Price

\$564.20

564.20

736.50

736.50

736.50

736.50

736.50 62.30

\$407.90

5/1

Resolution

.0004"

.0002"

.0004"

.0002"

.0004"

.0004"

.0004"

X-Pro Porta	X-Pro Portable Roughness Tester II		
Order No. 54-410-500-0 54-410-600-0	Description Portable Surface Roughness Tester .(Portable Surface Roughness Tester .)		
X-Pro Porta	ble Roughness Tester II Sta		
Order No. 54-400-896-0	Description Stand with Swivel Attachmen		
X-Pro Porta	ble Roughness Tester II Pro		
Order No.	Description		
54-400-319-0 54-400-326-0	General Purpose Probe General Purpose Probe		
54-420-321-0 54-420-327-0	Small Bore Probe Small Bore Probe		
54-420-301-0	Traverse Chisel Probe		
54-420-302-0	Parallel Chisel Probe		
54-420-328-0	Groove Bottom Probe		
54-420-120-0	AC Adapter Kit		
48	Prices & Specifications are		

.0004" probe (NIST specifications) .0002" probe (DIN specifications) and with Swivel nt obes and Accessories

	tment for mor
er No.	Description
10-500-0	Portable Surface
10-600-0	Portable Surface
ro Porta	ble Roughnes
er No.	Descrip
00-896-0	Stand w
ro Porta	ble Roughnes
er No.	Descri
00-319-0	Genera
~ ~ ~ ~ ~	0

ucpan	mem ioi
o Porta	ble Roug
r No.	Descripti
10-500-0	Portable S
10-600-0	Portable S
Dorta	ble Roug
	Die noug
r No.	C
0-896-0	S
. Deute	
o Porta	ble Roug
r No.	
00-319-0	(
00-326-0	





Fowler TOOL-A-THON

50

Steel Squares & Sets

- Made of the finest carbon tool steel, these economy squares have true right angles both inside and outside
- Beams and blades ground and lapped for straightness and parallelism
- Hardened blade
- Beam grooved at inner corner for clearance of burrs and dirt
- Squareness of blade edge to the working face: 2" & 3" = ±.0006", 4" & 6" = ±.0008" , 9" & 12" = ±.0012"

Blade Size	Beam Size
2"	1.5"
3"	2.5"
4"	3"
6"	4"
9"	6"
12"	8"

Sets come complete in a "Shop Hardened" molded case!

Order No.	Size/Description	List Price	Sale Price
52-432-444-0	3 Piece Square Set: 2", 4" & 6" with shop hardened case	\$57.20	\$49.20
52-432-246-0	4 Piece Square Set: 2", 3", 4" & 6" with shop hardened case	68.10	55.60
52-432-469-0	4 Piece Square Set: 4", 6", 9" & 12" with shop hardened case	114.30	105.80
52-432-004-0	4" Square only	20.60	17.50
52-432-006-0	6" Square only	22.90	18.80
52-432-009-0	9" Square only	45.80	39.70
52-432-012-0	12" Square only	77.80	66.40

Cylindrical Squares Used for checking squares, height gages and other instruments Hardened and the ends are lapped to 90° angular accuracy 6" cylindrical squares: ±.0001" 12" cylindrical squares: ±.00015" Includes handles and wood case

Order No. 52-750-006-0 52-750-012-0 Description 6" cylindrical square 12" cylindrical square

\$180.30 257.50

List Price

Sale Price

\$160.00

230.00

51

LER HIGH P

52-432-246-0

Volume 15.3

Tool Master Lite Tool Presetter

NEW!

Fowler's NEW Tool Presetter Stand for maximum productivity with ultimate user-friendliness. Tool Master Lite is a simple and user friendly presetter.

Swiss Quality!

Introductory Offer 15% off

User friendly

- Swiss quality
- Reduces setup times · Measures all types of tooling
- No connection to power or compressed air needed
- Needle bearing tool pot can be used with various adaptors, contact Fowler's technical department for details
- · Easy to use digital display for each axis
- · High concentricity needle bearing tool pot
- Maximum measuring repeatability
- · Smooth ball bearing guides

Technical Data

Measuring Range Accuracy (X and Z) Fine Adjustment **Tool Mounting** Measuring Method Dimensions Weight Power

X axis 9.8"/250mm, Z axis 11.8"/300mm .0008"/.02mm X axis Needle bearing SK 50 - standard Contact 420 x 150 x 590mm 23 kg Battery (AA type)

TOOL MASTER Lite

Tool Pot Adaptors are available.

Fowler

Contact the Fowler Technical Department for more information

Order No.	Description	List Price	Sale Price
54-188-777-0	NEW Tool Master Lite Tool Presetter	\$6998.90	\$5940.00

52





Fowler-Trimos V3, V4 & V5 Electronic Height Gages

The NEW Fowler-Trimos V3, V4 and V5 vertical measuring instruments have been developed for the most difficult workshop environments. Manufactured in their entirety in Switzerland, they guarantee a robust, precise and reliable product in the long run.

	, they guarantee		nu renable	
Iong run. • Measuring ranges 400mn • Extremely easy to use • "Black mask" display with • Electronically adjustable r • Battery life: approximately • Vast range of accessories • All adjustments possible v • Cast iron base for optimal • RS232 and USB interface • Air cushion (V4 and V5 O • Dual probe holders (V4 and • Carriage displacement: M (<i>V5 includes selectable</i> <i>displacement</i>) • Measures heights, diament Min/Max/Delta • Accessory measuring pro and provide excellent rep • Resolution: 0.0005"/0.000 • Repeatability (2s): 0.0000 All V Models Include: • Charging unit • Measuring insert with ruby • Probe holder elbow Ø 8m • Setting gage • User's manual • Test certificate	n, 700mm and 1100m user friendly functio neasuring force 0.75 40 hours (lithium-io vithout tools stability shy) anual manual or motorize ters, perpendicularity bes up to 340mm in eatability 11mm 8"0.002mm (Ø 0.00	nm ns s/1.5 (N) in batteries) Up To 10% ed carriage v, centerlines, length available	TRIMOS	54-191-440-0
V3	54-192-340-0	54-192-370-0		
Measuring Range Range with Probe inverted Max. Permissible Errors Frontal Squareness Deviation Air Cushion	16"/407mm 20"/508mm 0.00032"/0.008mm 0.0004"/0.010mm	28"/711mm 31.9"/812mm 0.00032"/0.008mm 0.0006"/0.015mm	Swiss Quality	ď
V4	54-191-440-0	54-191-470-0	Fowler	MA
Measuring Range Range with Probe inverted Max. Permissible Errors Frontal Squareness Deviation Air Cushion	16"/407mm 28.3"/719mm 0.0002"/0.005mm 0.0004"/0.010mm	28"/711mm 40.2"/1023mm 0.00028"/0.007mm 0.0006"/0.015mm ES	5 FIVE YEAR WARRANTY	Save 5% Probe Sets
V5	54-199-540-0	54-199-570	-0	54-199-590-0
Measuring Range Range with Probe inverted Max. Permissible Errors (µm) Frontal Squareness Deviation Air Cushion	16"/407mm 28.3"/719mm 0.0002"/0.005mm	28"/711mm 40.2"/1023m 2.5 + L(mr 0.00032"/.00 YES	n)/300	43.7"/1110mm 56"/1422mm 0.00043"/0.011mm
Order No. Descript		Range	List Price	Sale Price
	Height Gage	16"/407mm	\$4281.00	\$3950.10
	Height Gage Height Gage	28"/711mm 16"/407mm	4720.00 5639.00	4356.90 5206.70
	Height Gage	16"/407mm 28"/711mm	6560.00	5206.70 6056.40
	Height Gage	16"/407mm	6215.00	5570.00
54-199-570-0 NEW V5	Height Gage	28"/711mm	7365.00	6600.00
54-199-590-0 NEW V5 Probe Sets	Height Gage	43"/1100mm	11393.00	10200.00
	cro Probe Set		1647.00	1547.00

54-199-106-0

54-199-107-0

16 pc. Macro Probe Set

7 pc. Economy Probe Set

Prices & Specifications are subject to change without notice.

1229.00

324.00

1129.00

307.80

mos e

The Fowler-Trimos innovative horizontal instrument that fulfills current quality requirements for many applications.



Multiple accessories ensure versatile applications for checking all types of gages such as plug gages, ring gages, thread plug gages, lever dial indicators, etc. as well as precision manufactured parts. Measuring range 2" and application range 4".

High accuracy is guaranteed by perfect instrument construction and the Heidenhain measuring system. The simplicity of the instrument and its ease of use allows precise and quick performance of all measurements. Adjustable Measuring Force is suitable for measuring thread members utilizing the 3 wire method.



THV Package 2

Specifications:

Specifications.	
Overall Application Range	Using standard probe
External measurement	0 - 4" /0 - 100mm
Internal measurement	.4 - 4" /10 - 100mm
Scale Range (travel)	Absolute display over 2"/50mm
Max. Measuring Band Error	0.000016"/.4µm reference
Temperature 20°C	
Resolution on Heidenhain ND 287	0.00001", 0.000001"
Repeatability	0.000005" ±2s (.1µm)
Adjustable Measuring Force	0 to 12N (0-40 oz.)



22,677.50

Package 1 include	6	
Part No. 54-198-558-0 54-198-115-0 54-198-110-0	Description THV w/floating table Measuring Table for Plug Gages Display Unit Quadra Check	<i>List Price</i> \$17,163.90 5,665.00 3,330.00
Package 2 include	6	
Part No. 54-198-508-0 54-198-115-0 54-198-110-0	Description THV w/standard table Measuring Table for Plug Gages Display Unit Quadra Check	<i>List Price</i> \$13,682.50 5,665.00 3,330.00
Description THV Package 1	List Price \$26,158.90	

18,662.00

/olume 15.3

Prices & Specifications are subject to change without notice.

