CHIEFTAIN R

The Foremost Chieftain vehicles are versatile, 4-tracked articulated off-highway transporters. Utilizing proven power train components and heavy duty center-frame steering, these high flotation vehicles provides economic transportation of heavy payloads in moderate to severe terrain conditions. The Chieftain can be readily adapted for all chassis-mounted or specialized equipment for superior off-road mobility. It is ideal for logistical support of remote drilling operations and pipeline or power line construction projects faced with severe terrain challenges.



FOREMOST CHIEFTAIN R

PERFORMANCE

Payload 30,000 lbs 13,600 kg Tare 51,700 lbs 23,450 kg **Gross Vehicle Weight** 81,700 lbs 37,058 kg 28.5' **Turning Radius** 8.7 m **Maximum Speed** 20 mph 32 km/h **Fording Depth** 4' 6" 1.37 m **Maximum Gradeability** Forward 50% Side 30%

GROUND PRESSURE AT 6" PENETRATION

| 0 tons | 2.8 psi | 19.3 kPa |
|---------|---------|----------|
| 5 tons | 3.3 psi | 22.8 kPa |
| 10 tons | 3.8 psi | 26.2 kPa |
| 15 tons | 4.4 psi | 30.3 kPa |

ENGINE

Make Cat Model C9

 Type
 EPA Tier III 6 cyl diesel engine

 Horsepower @ 2100 RPM
 375 hp
 280 kW

 Torque @ 1400 rpm
 988 ft-lb
 1340 N-m

SUSPENSION

Type Independent airbag suspension at each wheel

Hubs Oil bath with metal face seals

TRACKS

Type Rubber track w/ bias steel cord
Width 34" 864 mm

DIMENSIONS

| Length | 37' 6" | 11.5 m |
|-------------|--------|--------|
| Width | 9' | 2.7 m |
| Height | 9' 7" | 2.9 m |
| Deck Length | 18' | 5.5 m |
| Deck Width | 8' | 2.4 m |

OPTIONAL DECK EQUIPMENT

Digger Derricks Vibrosource equipment aerial man lifts

Cranes, Stiff & Knuckle Boom mechanic shacks

ELECTRICAL SYSTEMS

IQAN Control System

Voltage 12V Alternator Capacity 100 A

Battery Capacity 2 Deltco 1151, 580 cca

WHEELS
7.50 x 20 Permafitted

STEERING
Hydrostatic Drive System - Single 360° joystick. 2 Stage planetary track drives. Counter rotation capability.

CHASIS
All welded construction, high strength steel for higher durability and lower weight

CAPACITIES
Fuel Tank - 100 US gal (379 L) Hydraulic Tank - 45 US gal (170 L)

OTHER
OPTIONS

Air Conditioning

I man, 2man or 8 man cab
Tapered front end
Front blade
Front blade
Frame extension

Unit can be altered for high ground clearance