

HUSKY 4

.....

The Husky 4 provides increased mobility over adverse terrain conditions such as sand, mud, muskeg, swamp and snow, where conventional excavators would encounter difficulty. Using proven technology from the Foremost Husky 8, the Husky 4 provides a mating platform to suit most OEM 200 series excavators. The OEM excavator uses the hydraulic power to propel the Husky 4 undercarriage.



FOREMOST



PRODUCT INFORMATION

FOREMOST HUSKY 4

PERFORMANCE

Weights

| | | |
|-------------------------|------------|-----------|
| Undercarriage | 27,716 lbs | 12,571 kg |
| CAT 320D | 30,723 lbs | 13,936 kg |
| Operating Weight | 58,439 lbs | 26,507 kg |

| | | |
|-----------------------------|-----------------|--------------------|
| Turning Radius | 0 in | 0 m |
| Maximum Speed | 3.2 mph | 5.2 km/h |
| Fording Depth | 48 in | 1.22 m |
| Maximum Gradeability | Side 40% 22° | Forward 60% 31° |
| Drawbar Pull | 54,266 lbf | 24,614 kgf |
| Ground Pressure* | 3.42 PSI | 23.58 kPa |

*Based on 6 in (152 mm) penetration.

HYDROSTATIC TRANSMISSION

| | |
|---------------------------|--------------------------------------|
| Hydrostatic Motors | Rexroth, axial-variable displacement |
| Planetaries | Rexroth L & S |

SUSPENSION & WHEELS

| | |
|---------------|--------------------------------------|
| Type | Walking beam |
| Hubs | Oil bath with metal face seals |
| Wheels | 10:00 x 20 - 14 ply, pneumatic solid |

TRACKS

| | | |
|-------------------|--------|----------|
| Type | D-dent | |
| Width | 56" | 1,422 mm |
| Belt Width | 20" | 508 mm |
| Belt Ply | 5 ply | |

DIMENSIONS

| | | |
|-----------------------------|---------|----------|
| Length | 431 in | 10.9 m |
| Width | 157 in | 3,988 mm |
| Width without tracks | 123 in | 3,124 mm |
| Height | 125 in | 3,175 mm |
| Height Under | 150 in | 3,810 mm |
| Ground Clearance | 21.5 in | 546 mm |

WORKING RANGE

| | | |
|---------------------------|-------------|---------|
| Max. Digging Depth | 23 ft 11 in | 7.30 m |
| Max. Reach | 34 ft 7 in | 10.55 m |

OPTIONAL EQUIPMENT

| | |
|---------------------------|--------------------------------------|
| Hydrostatic Motors | Rexroth, axial-variable displacement |
| Planetaries | Rexroth L & S |

OTHER OPTIONS

- Arctic heating package
- Positive air Diesel Engine shut off
- Beacon
- Search light

Note: Information is provided based on a CAT320D Excavator. Adapter plates for various 200 series excavators are available. Consult your Foremost representative for more information.

