

8128H

WHEEL LOADER





## 8128H SPECIFICATIONS >>>



MAIN SPECIFICATION	The street of th
Operating Weight	50,600 kg
Gross Power	391 kW (525 hp)
Standard Bucket Size	7 m³
Loading Capacity	12,000 kg
Max. Pull	358 kN
Standard breakout force	385 kN
Fastest Total Cycle Time	13.2 s
Dump Height at Full Discharged	3,910 mm
Configuration	Cummins QSK19 Tier3 Engine/DANA transmission and torque converter/Kessler axle/Parker pump and valve/Standard boom/CFC-free air conditioner/Auto central lubrication/Grammer seat
Features	High Power Performance  Multiple engine models: economic, standard, powerful  Perfect match of Cummins electronic controlled engine and ZF full-automatic transmission achieve great performance in severe heavy loading;  ZF axles with slip limited differentials.  Efficient Hydraulic System  Load-sensing hydraulics with piston pumps  Electrical proportion valve applied in finger lever control  Fully hydraulic wet discs brake with dual pedals

## Guangxi Liugong Machinery Co., Ltd.

No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China T: +88 772 3885124 E: overseas@liugong.com www.liugong.com