

970E

EXCAVATOR

 **LIUGONG**



970E SPECIFICATIONS >>>



MAIN SPECIFICATION

Operating weight- metric tons	70,500 kg
Rated power	354 kw @ 1,800 rpm
Standard bucket capacity	4.3 m ³
Optional bucket capacity	3.7-5.2 m ³
Swing speed	6.9 rpm
Travel speed Low / High	4.6/2.9 km/h
Drawbar pull	460 KN
Shoe ground pressure	101 KPa
Configuration	Cummins QSX15 Tier II Engine/KPM main pump/ KPM main valve/KPM swing motor & reduction/ Nabtesco travel motor & Bonfiglioli reduction/Casappa hydraulic fan system

Features

- IPC system (Intelligent Power Control)
LiuGong new-generation computer aided power control system with independent intellectual property rights. Integrates hydraulic systems leads to high efficiency, fuel saving and better control ability.
- 6 working mode. Multiple modes of operation, 6 modes and 12 switches to adapt to a variety of conditions demand.
- Cooling fan.
The hydraulically-driven, electronically controlled cooling fan regulates the temperature of the vital components and reduces sound level.
- Use adjustable undercarriage, convenient for transport.

Guangxi Liugong Machinery Co., Ltd.

No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China
T: +86 772 3886124 E: overseas@liugong.com
www.liugong.com

Specifications and designs are subject to change without notice. Machines shown may include optional equipment.