PFT-N REBAR BENDERS



- Full clock wise (CW) and counterclockwise (CCW) continuous table rotation.
- Supplied with tool-set for stirrups, bending bracket, plus a full selection of pins and rollers
- Heavy duty cast steel shear head with electric safety cover
- Foot pedal control
- Dual adjustable rails for hold back pins
- Large diameter turntables
- Angles are easily adjusted by changing pin position, or by rail adjustment.
- Available in variable speed, 8-16 rpm
- Optional end rollers on table

Available Spiral / Hoop Attachments



HEAVY DUTY ROTARY STYLE MECHANICAL BENDER AND SHEAR



MODEL	MAX CAPACITY			RPM	MOTOR (HP)	SIZE (")	WEIGHT (lbs)
PFT 32/26N	#6	20M	3/4"	9	2	32X35X34	705
PFT 38/30N	#8	25M	1"	8	2.5	35X39X34	950

DIGITAL CONTROLS

9x9 Control

Up to 9 different angles can be pre-set on the machine through "PIN" placement. Operator selects the sequence of bends required from the control console.



10/50 Control

With memory for bar shapes. Automatic sequencing. Digital angle entry with fast, easy adjustment.



*Digital panel can be turned off at any time with machine reverting to a single angle preset system If the panel fails or is unneccesary for the job, you can still bend with full control and accuracy.