Serving Industry Since 1919



CURVED BLADE CUTTERS for SCRAP and DEMOLITION



<u>MODEL PART # DESCRIPTION POWER FORCE OPENING PRESSURE M</u>	<u>WEIGHT</u>
--	---------------

F130N series is recommended for intermittent cutting, light duty scrap and demo applications

			<u> </u>				
F130N T30	#1502600	Curved Blades	115 Volts	35T	5.1"	7980 PSI	33 lbs
F130N T30	#1502521	Curved Blades	18V Battery	35T	5.1"	7980 PSI	27 lbs
F130N T30	#1502604	Curved Blades	36V Battery	35T	5.1"	7980 PSI	28 lbs
F130N T30	#1502596	Curved Blades	Gasoline	35T	5.1"	7980 PSI	35 lbs

F150N series is recommended for intermittent cutting, heavy duty scrap and demo applications

F150N T40	#1502591	Curved Blades	115 Volts	44T	5.7"	10000 PSI	44 lbs
F150N T40	#1502658	Curved Blades	18V Battery	44T	5.7"	10000 PSI	43 lbs
F150N T40	#1502602	Curved Blades	Gasoline	44T	5.7"	10000 PSI	48 lbs
F130N T25	#1502055	Curved Blades	Hydraulic	25T	5.1"	10000 PSI	26 lbs
F145N T30	#1502049	Curved Blades	Hydraulic	30T	5.7"	10000 PSI	40 lbs
F170N T80	#1502033	Curved Blades	Hydraulic	80T	6.7"	10000 PSI	54 lbs

F130/145/170 Hydraulic tools require pump and hose for their operation. Not included in price Available as complete portable systems with pump, hose and mobile cart. Please inquire



GENSCO AMERICA, INC. ACROSS USA 800 268-6797

5307 Dividend Dr., Decatur, Georgia 30035 • Tel: 770 808-8711 • Fax:770 808-8739 GENSCO EQUIPMENT (1990) Inc

53 Carlaw Ave., Toronto, Canada M4M 2R6 • Tel: 416 465-7521 • Fax:416 465-4489 email: info@genscoequip.com • url: www.genscoequip.com



F-130N

UNI EN13204:2004 CATEGORY E

Material	Profile	Size (mm)	Size (inches)
S235JR	٠	Ø 22	0.75 - (3/4)
S235JR		80X8	3 X ¼
S235JR		45X45X4	1.75 X 1.75 X 1/8
S235JR		50X30X3	2 X 1 1/8 X 1/8
S235JR	0	Ø 48.3X2.9	2 X 1/8 WALL



F-150N

MDC360 T40 36V - UNI EN13204:2004 CATEGORY H

Material	Profile	Size (mm)	Size (inches)
S235JR	•	Ø 30	1
S235JR		110X10	4 ¼ X 3/8
S235JR		60X60X4	2 ¼ X 2 ¼ X 1/8
S235JR		80X40X4	3.14 X 1 ½ X 1/8
S235JR	0	Ø 76.1X4	3 X 1/8 WALL