


Hydraulica 6000

[VGL99]

The Hydraulica 6000 is the largest capacity glass vacuum lifter in the UK to date. With a maximum capacity of 6000kg, this vacuum sucker features 360° electric powered rotation and 90° hydraulic tilt to assist in the manoeuvring of large, heavy loads.

This quad-circuit window sucker features four independent vacuum circuits and can be configured to lift different sized loads, making it extremely versatile for consideration on a wider range of large capacity projects.

The Hydraulica 6000 is complete with cable remote control, extension arms and a transport stand as standard, with a radio remote control available as an optional accessory. This leading glass vacuum lifter offers quicker, safer, high capacity lifting on site.



Key Features

- Capacity: 6000kg
- Four vacuum circuits with 4 on-board maintenance free vacuum pumps
- Electric powered 360° rotation
- 90° hydraulic tilt
- Audio-visual low vacuum alert
- Transport stand as standard
- Cable remote control as standard, optional radio remote
- Sliding extension arms

Reference Code VGL99

© GGR Group Ltd 2016



SOUTH Units 8 - 10 Ridgeway
Drakes Drive
Long Crendon Industrial Estate
Bucks · HP18 9BF · UK
PHONE +44 (0)1844 202 071
FAX +44 (0)1844 202 075

NORTH Presentation House
Broadgate
Broadway Business Park
Oldham · OL9 0JA · UK
PHONE +44 (0)161 683 2580
FAX +44 (0)161 683 4444

SCOTLAND Unit 11 · 3rd Road
Blantyre Industrial Estate
Blantyre
Glasgow · G72 0UP · UK
PHONE +44 (0)1698 824 444
FAX +44 (0)1698 824 488

EMAIL info@ggrgroup.com
WEB www.ggrgroup.com

GGR Group Limited
Company Registration Number 04901075
VAT Registration Number 989811160

Technical Specification

Safe Working Load (smooth, clean surface at 60% vacuum)	capacity:	6000kg
Number of suction cups	standard	20
Suction cup	description:	black rubber, not abrasion resistant, heat resistant up to 100°F
Suction cup diameter	standard:	520mm
Suitable for lifting	material properties: surface: example:	gastight / non-porous smooth glass, plastic boards, ceramic plates, sheet metals
Weight of lifter	standard approx:	1800kg
Depth of lifter	standard:	550mm
Rotation	rotation:	360° electric powered
Tilt	tilt:	90°
Vacuum system	dual circuit:	4 pumps,
Voltage	pump: battery charger:	24v DC from rechargeable batteries (2 x50Ah in total) 115v/230v 50/60Hz single phase factory selectable
Standard Accessories	standard:	Cable remote control, extension arms, transport stand
Optional Accessories	optional:	Radio remote control

Dimensions

