49

<u>lift Concave & Convex</u>

DSL2 Curved Glass Lifter [400kg]

The DSL2 dual circuit lifter is a first-rate machine for lifting all forms of curved glass and plastics weighing up to 400kg. Including flexible arms that can swivel back and forth, the DSL2 vacuum lifter can 'mould' itself to convex and concave sheets.

The DSL2 is loaded with extra safety features including two independent vacuum circuits, each designed to handle a load on its own, as well as an audio-visual low vacuum alarm. This machine is a popular device for the safer handling of curved toughened and laminated architectural glass.

This specialist glazing installation equipment comes with manual 270° lockable rotation, as well as manual lockable tilting from flat to upright position for seamless handling of heavy loads.

Key Features

- Capacity: 400kg
- Dual circuit vacuum system with reserve tank, non-return valve and vacuum gauge for each circuit
- · Two or four integral maintenance-free vacuum pumps
- 90° manual tilt lockable at vertical and horizontal
- Manual 270° lockable rotation
- Two 12v batteries with integral charger or 110v/240v mains and battery energy gauge
- Audio-visual low vacuum warning
- Pad arms swivel for handling both concave and convex materials
- On-board control panel







Reference Code VGL23

Technical Specifications

| Safe working load (smooth, clean surface at 60% vacuum) | capacity: | 400kg |
|--|--|---|
| Number of suction cups | cups: | 16 |
| Suction cup | description: | black rubber, not abrasion resistant, heat resistant up to 100°F |
| Suction cup diameter | diameter: | 220mm |
| Suitable for lifting | material properties: surface: example: | gastight / non-porous smooth glass, plastic boards, sheet metals, coated boards |
| Weight of lifter | approx: | 130kg |
| Depth of lifter | depth: | 300mm |
| Rotation | rotation: | 135° manual left & right lockable |
| Tilt | tilt: | 90° manual lockable |
| Vacuum system | dual circuit: | 2 or 4 pumps, 2 vacuum reserve tanks |
| Voltage | pump: battery charger: | 12v DC from rechargeable batteries 110v/240v 50/60Hz single phase factory selectable |
| Optional accessories | optional: | cable remote control, radio remote control |
| | | |



