INFRARED PROCESS METER



Model KJT 400





Tomorrow's Testing, Today ! 1-800-438-5388

Infrared Process Meters

Instant Non-Contact Process Measurement

This simple-to-use device allows the user to conduct accurate continuous measurements of product components -- without sampling, product contact or degradation. Using the principle of near-infrared reflectance, items such as moisture, fat, protein, film thickness and carbon content (BTU) can be monitored and process control automated. friction on a variety of substances.

We can measure on conveyors, augurs, drop chutes, pneumatic transport and gravity feeds. In addition, our precision allows measurement through sight glasses into process vessels such as spray dryers, fluid-bed dryers, calcincers and rotary granulators. If we can see the product, we can accurately measure it!

The ability to test in almost any situation opens new doors to product and process assessment. R&D personnel can easily analyze formulations during production, not just in laboratory settings. Manufacturing personnel can measure products on the production line, improving quality assessment and production throughput.

Simple Operation

Once calibrated, the KJT400 is simply aimed at the surface of the liquid or solid to be measured and light is absorbed by the chemical components to be measured. The detected absorbance is converted into component values. Up to 100 product calibrations are stored in each measurement head, allowing measurement at multiple points on a process, or, different processes, by simply unbolting the four mounting bolts, moving the head to the new location, rebolting, and connecting to AC power.

Designed for Years of Stable Use

Integrated temperature/humidity compensation, air purge capability, Nema 4 housing (explosion proof), sealed electrical connectors, and custom built components give you with the assurance that these meters will provide years of use. To maintain calibration over the life of the instrument, simply insert the included "zero plate" and the KJT400 system will be brought back to baseline measurement in less than five seconds.

We stand behind our KJT400 systems with a full **One-Year** guarantee on parts and labor. Kett's dependable quality allows you to productively focus on improving your product's quality, not waste time calibrating and verifying our gauges.

Full Complement

Offering a complete line of NIR testing systems, we have desktop units for lab or near-line use and the world's first and only handheld portable. If you need to measure product constituents, wish to place an order, or, if you require additional guidance on model selection, please call toll-free!

Tomorrow's Testing, Today!

Kett offers a complete line of innovative measurement devices —— for laboratory, field, and commercial applications. If your company needs fast, accurate measurements, please call Kett!



Specifications

specifications	
Model	KJT-400
Measurement Range	0-100%
Measurement Distance	350 +/- 50 mm
Measurement Diameter	35-50mm
Response Time	Instant
Refresh Rate	.5 Seconds
Analytica l Curves	100
Ambient Temperature	0 - 40 C
Ambient Humidity	0 - 90% RH
Accuracy	+/1% or better
	(reference-dependent)
Precision	To 0.001% nominal
Power Source	110 VAC
Display	
%	Y
Head Number	Y
Channel	Y
Error Codes	Y (41 - 1
Measuring Principle	NIR Reflectance/Absorbance
Light Source	Tungsten Lamp
Detector	Lead Sulfide
Display Type	LED Digital
Communications	Backlit LCD RS232C
community	
Remote Control	Y
Weight (Net / Shipment)	17/45 bs
Dimensions (mm)	14/40lbs (Processor) 432Hx150Wx289D
	432Hx150Wx289D 248Hx157Wx320D (Processor)
Warranty	One Year Parts and Labor
	Maintenance Agreements
	Available
	1 Avenue

1-800-GET-KETT 1-800-438-5388