

# UCS(F)...

zone 1	zone 2	Ex de II	II2GD	-40°C	T4 (130°C)	-20°C	T6 (80°C)
zone 21	zone 22	Ex e [ia] IIC	II2(1)GD	+80°C		+40°C	
		Ex ia IIC	II2GD			-40°C	T5 (95°C)
			IP66			+60°C	

EMERGENCY PUSH-BUTTON WITH PROTECTION LIFT FLAP

PULSANTE DI EMERGENZA CON PROTEZIONE LIFT FLAP

<b>Caratteristiche:</b>	Pulsante di allarme antincendio UCS(F)..., protezione ATEX (Exde), con protezione LIFT FLAP. <b>MODI DI FUNZIONAMENTO</b> Manuale: (doppia azione)
	Manuale: (doppia azione) I contatti devono essere azionati alzando lo sportello e premendo il pulsante
	Manuale: (doppia azione) I contatti devono essere azionati alzando lo sportello e premendo il pulsante ( <b>push-push</b> )
	Manuale: (doppia azione) I contatti devono essere azionati alzando lo sportello e premendo il pulsante ( <b>illuminato</b> )
<b>Features:</b>	Fire alarm station UCS(F)..., model of protection ATEX (Exde), with protection LIFT FLAP. <b>MODE OF OPERATION</b> Manual: (double action)
	Manual: (double action) The contacts must be operated raising the flap and pressing the button
	Manual: (double action) The contacts must be operated raising the flap and pressing the button ( <b>push-push</b> )
	Manual: (double action) The contacts must be operated raising the flap and pressing the button ( <b>illuminated</b> )

Specifica tecnica - Technical specification	
<b>Materiale</b> Material	<b>UCS(F)...A</b> Alluminio - Aluminium <b>UCS(F)...G</b> GRP glass fibre reinforced polyester <b>UCS(F)...S</b> Acc. Inox - Stainless steel 304/316
<b>Dimensioni</b> Dimension	<b>UCS(F)...A</b> 110x110x85mm (alternative dimension 170x110x83) <b>UCS(F)...G</b> 110x110x85mm (alternative dimension 170x110x85) <b>UCS(F)...S</b> 110x110x100mm (alternative dimension 200x100x100)
<b>Colore</b> Color	Rosso (altri a richiesta) Red (other on request)
<b>Imbocchi</b> Cable entries	1 gland M20 std execution <b>on request:</b> 1 gland M25 2 gland M20 or M25

Spring return, flush actuator	"Push-button" illuminated			<b>Features of the Contact 10 A</b> <b>Caratteristiche dei contatti 10 A</b>  Ith = 10 A; Ui = 415 V <b>AC</b> Ue = 380 V; Ie = 1,9 A or Ue = 240 V; Ie = 3 A or Ue = 120 V; Ie = 6 A <b>DC</b> Ue = 250 V; Ie = 0,27 A or Ue = 125 V; Ie = 0,55 A or Ue = 24 V; Ie = 2,87 A
"Push-push" to release, flush actuator				

<b>COLOR AVAILABLE</b> <b>COLORI DISPONIBILI</b>  <b>BIANCO - WHITE</b> <b>NERO - BLACK</b> <b>VERDE - GREEN</b> <b>ROSSO - RED</b> <b>GIALLO - YELLOW</b> <b>BLU - BLUE</b>			

ALTRE ESECUZIONI SPECIALI A RICHIESTA  
OTHER SPECIAL EXECUTION ON REQUEST

6 Contatti manuali Doppia azione (LIFT FLAP) Manual contact Double action (LIFT FLAP)	
UCS(F)-21A	1 NO
UCS(F)-22A	1 NC
UCS(F)-25A	1 NC + 1 NO
UCS(F)-27A	2 NC
UCS(F)-29A	2 NO
UCS(F)-30A	1 NO + 2 NC
UCS(F)-31A	1 NC + 2 NO
UCS(F)-32A	3 NC
UCS(F)-33A	3 NO

6 Contatti manuali Doppia azione (LIFT FLAP) Manual contact Double action (LIFT FLAP)	
UCS(F)-21G	1 NO
UCS(F)-22G	1 NC
UCS(F)-25G	1 NC + 1 NO
UCS(F)-27G	2 NC
UCS(F)-29G	2 NO
UCS(F)-30G	1 NO + 2 NC
UCS(F)-31G	1 NC + 2 NO
UCS(F)-32G	3 NC
UCS(F)-33G	3 NO

6 Contatti manuali Doppia azione (LIFT FLAP) Manual contact Double action (LIFT FLAP)	
UCS(F)-21S	1 NO
UCS(F)-22S	1 NC
UCS(F)-25S	1 NC + 1 NO
UCS(F)-27S	2 NC
UCS(F)-29S	2 NO
UCS(F)-30S	1 NO + 2 NC
UCS(F)-31S	1 NC + 2 NO
UCS(F)-32S	3 NC
UCS(F)-33S	3 NO

10 Contatti manuali Doppia azione (LIFT FLAP) Manual contact Double action (LIFT FLAP) pulsante (push-push) button (push-push)	
UCS(F)-21A	1 NO
UCS(F)-22A	1 NC
UCS(F)-25A	1 NC + 1 NO
UCS(F)-27A	2 NC
UCS(F)-29A	2 NO
UCS(F)-30A	1 NO + 2 NC
UCS(F)-31A	1 NC + 2 NO
UCS(F)-32A	3 NC
UCS(F)-33A	3 NO

10 Contatti manuali Doppia azione (LIFT FLAP) Manual contact Double action (LIFT FLAP) pulsante (push-push) button (push-push)	
UCS(F)-21G	1 NO
UCS(F)-22G	1 NC
UCS(F)-25G	1 NC + 1 NO
UCS(F)-27G	2 NC
UCS(F)-29G	2 NO
UCS(F)-30G	1 NO + 2 NC
UCS(F)-31G	1 NC + 2 NO
UCS(F)-32G	3 NC
UCS(F)-33G	3 NO

10 Contatti manuali Doppia azione (LIFT FLAP) Manual contact Double action (LIFT FLAP) pulsante (push-push) button (push-push)	
UCS(F)-21S	1 NO
UCS(F)-22S	1 NC
UCS(F)-25S	1 NC + 1 NO
UCS(F)-27S	2 NC
UCS(F)-29S	2 NO
UCS(F)-30S	1 NO + 2 NC
UCS(F)-31S	1 NC + 2 NO
UCS(F)-32S	3 NC
UCS(F)-33S	3 NO

14 Contatti manuali Doppia azione (LIFT FLAP) Manual contact Double action (LIFT FLAP) Pulsante illuminato a led Led illuminated Push button	
UCS(F)-21A	1 NO
UCS(F)-22A	1 NC
UCS(F)-25A	1 NC + 1 NO
UCS(F)-27A	2 NC
UCS(F)-29A	2 NO
UCS(F)-30A	1 NO + 2 NC
UCS(F)-31A	1 NC + 2 NO
UCS(F)-32A	3 NC
UCS(F)-33A	3 NO

14 Contatti manuali Doppia azione (LIFT FLAP) Manual contact Double action (LIFT FLAP) Pulsante illuminato a led Led illuminated Push button	
UCS(F)-21G	1 NO
UCS(F)-22G	1 NC
UCS(F)-25G	1 NC + 1 NO
UCS(F)-27G	2 NC
UCS(F)-29G	2 NO
UCS(F)-30G	1 NO + 2 NC
UCS(F)-31G	1 NC + 2 NO
UCS(F)-32G	3 NC
UCS(F)-33G	3 NO

14 Contatti manuali Doppia azione (LIFT FLAP) Manual contact Double action (LIFT FLAP) Pulsante illuminato a led Led illuminated Push button	
UCS(F)-21S	1 NO
UCS(F)-22S	1 NC
UCS(F)-25S	1 NC + 1 NO
UCS(F)-27S	2 NC
UCS(F)-29S	2 NO
UCS(F)-30S	1 NO + 2 NC
UCS(F)-31S	1 NC + 2 NO
UCS(F)-32S	3 NC
UCS(F)-33S	3 NO


**ALTRE ESECUZIONI SPECIALI A RICHIESTA  
OTHER SPECIAL EXECUTION ON REQUEST**

**ESEMPIO - EXAMPLE**  
Dimensione alternativa jbox  
con LED e/o EOL e/o MORSETTIERA e/o SUNSHADE  
Alternative dimension jbox  
with LED and/or EOL and/or TERMINAL and or SUNSHADE

**LED PILOT LIGHT**

**LED LIGHTS**  
24V to 254 V AC/DC  
2 to 10 mA


(W) WHITE	(G) GREEN
(R) RED	(Y) YELLOW
(B) BLUE	



**LED LIGHT**

**EOL  
(CBR) RESISTOR  
(CBD) DIODE  
SERIES or PARALLEL**

12—240V AC/DC  
MAX 4W (to be defined)



**SUNSHADE**



**EOL  
RESISTOR**